



# MATERIAL SAFETY DATA SHEET

Squeak Relief™

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Squeak Relief™  
**Product Number:** 90201, 90031  
**Product Use:** Lubricant.  
**Manufacturer/Supplier:** International Lubricants, Inc.  
P.O. Box 24743  
Seattle WA 98124-0743, USA  
**Phone Number:** (206) 762-5343  
(800) 333-LUBE (5823)  
**Emergency Phone:** CHEM TEL (800) 255-3924  
CHEM TEL (813) 248-0585  
**Date of Preparation:** February 5, 2009

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

DANGER

EXTREMELY FLAMMABLE. HARMFUL BY INHALATION. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

**Eye:** May cause eye irritation.  
**Skin:** May cause skin irritation.  
**Ingestion:** Not a normal route of exposure. Harmful: may cause lung damage if swallowed.  
**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Medical Conditions Aggravated By Exposure:** Asthma. Allergies.

**Target Organs:** Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredient                               | CAS #      | Wt. %     |
|--|------------|-----------|
| Acetone                                  | 67-64-1    | 30 - 60   |
| Aluminum, elemental                      | 7429-90-5  | 10 - 30   |
| Stoddard solvent                         | 8052-41-3  | 7 - 13    |
| Sulfonic acids, petroleum, calcium salts | 61789-86-4 | 0.5 - 1.5 |
| Propane                                  | 74-98-6    | 10 - 30   |



# MATERIAL SAFETY DATA SHEET

Squeak Relief™

## Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

- Flammability:** Flammable by WHMIS/OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.
  - Unsuitable Extinguishing Media:** Direct water spray.
- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
  - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.
- Environmental Precautions:** Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Clean-Up:** Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak. Allow gas to dissipate harmlessly into the atmosphere.
- Other Information:** Not available.



# MATERIAL SAFETY DATA SHEET

Squeak Relief™

## Section 7: HANDLING AND STORAGE

### Handling:

Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

### Storage:

Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Do not store at temperatures above 49 °C.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

| Ingredient                               | Exposure Limits      |                      |
|--|----------------------|----------------------|
|  | OSHA-PEL             | ACGIH-TLV            |
| Acetone                                  | 1000 ppm             | 500 ppm              |
| Aluminum, elemental                      | 15 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> |
| Stoddard solvent                         | 100 ppm              | 100 ppm              |
| Sulfonic acids, petroleum, calcium salts | Not available.       | Not available.       |
| Propane                                  | 1000 ppm             | 1000 ppm             |

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### Personal Protective Equipment:

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

|                          |                         |
|--------------------------|-------------------------|
| <b>Appearance:</b>       | Opaque.                 |
| <b>Color:</b>            | Silver                  |
| <b>Odour:</b>            | Aromatic.               |
| <b>Odour Threshold:</b>  | Not available.          |
| <b>Physical State:</b>   | Gas/Pressurized Liquid. |
| <b>pH:</b>               | Not available.          |
| <b>Viscosity:</b>        | Not available.          |
| <b>Freezing Point:</b>   | Not available.          |
| <b>Boiling Point:</b>    | ~ -18 °C (~ -0.39 °F)   |
| <b>Flash Point:</b>      | Not available.          |
| <b>Evaporation Rate:</b> | Not applicable.         |



# MATERIAL SAFETY DATA SHEET

Squeak Relief™

|   |                |
|---|----------------|
| <b>Lower Flammability Limit:</b>              | Not available. |
| <b>Upper Flammability Limit:</b>              | Not available. |
| <b>Vapor Pressure:</b>                        | 2 mm           |
| <b>Vapor Density:</b>                         | Not available. |
| <b>Specific Gravity:</b>                      | 0.5-0.65       |
| <b>Solubility in Water:</b>                   | Negligible.    |
| <b>Coefficient of Water/Oil Distribution:</b> | Not available. |
| <b>Auto-ignition Temperature:</b>             | Not available. |
| <b>Percent Volatile, wt. %:</b>               | Not available. |
| <b>VOC content, wt. %:</b>                    | Not available. |

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** Oxidizers.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

| <b>Ingredient</b>                        | <b>LD<sub>50</sub> (oral)</b> | <b>LC<sub>50</sub></b>            |
|--|-------------------------------|-----------------------------------|
| Acetone                                  | 5800 mg/kg, rat               | Not available.                    |
| Aluminum, elemental                      | Not available.                | Not available.                    |
| Stoddard solvent                         | > 5000 mg/kg, rat             | > 5500 mg/m <sup>3</sup> 4hr, rat |
| Sulfonic acids, petroleum, calcium salts | Not available.                | Not available.                    |
| Propane                                  | Not available.                | Not available.                    |

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Ingestion:** Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

### EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Not available.

**Chronic Effects:** Not hazardous by WHMIS/OSHA criteria.

**Carcinogenicity:** Not hazardous by WHMIS/OSHA criteria.



# MATERIAL SAFETY DATA SHEET

Squeak Relief™

## Ingredient

Acetone  
Aluminum, elemental  
Stoddard solvent  
Sulfonic acids, petroleum, calcium salts  
Propane

## Chemical Listed as Carcinogen or Potential Carcinogen \*

Not listed.  
Not listed.  
Not listed.  
Not listed.  
Not listed.

\* See Section 15 for more information.

**Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.

**Reproductive Effects:** Not hazardous by WHMIS/OSHA criteria.

### Developmental Effects:

**Teratogenicity:** Not hazardous by WHMIS/OSHA criteria.

**Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.

**Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Skin Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

## Section 14: TRANSPORTATION INFORMATION

### DOT Classification

ORM-D

### TDG Classification

Limited Quantity

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).



# MATERIAL SAFETY DATA SHEET

Squeak Relief™

## SARA Title III

| Ingredient                                  | Section 302<br>(EHS) TPQ<br>(lbs.) | Section 304<br>EHS RQ (lbs.) | CERCLA<br>RQ (lbs.) | Section<br>313 |
|---|------------------------------------|------------------------------|---------------------|----------------|
| Acetone                                     | Not listed.                        | Not listed.                  | 5,000               | 313            |
| Aluminum, elemental                         | Not listed.                        | Not listed.                  | Not listed.         | 313            |
| Stoddard solvent                            | Not listed.                        | Not listed.                  | Not listed.         | Not listed.    |
| Sulfonic acids, petroleum,<br>calcium salts | Not listed.                        | Not listed.                  | Not listed.         | Not listed.    |
| Propane                                     | Not listed.                        | Not listed.                  | Not listed.         | Not listed.    |

## State Regulations

### California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

## Global Inventories

| Ingredient                               | Canada<br>DSL/NDSL | USA<br>TSCA |
|--|--------------------|-------------|
| Acetone                                  | DSL                | Yes.        |
| Aluminum, elemental                      | DSL                | Yes.        |
| Stoddard solvent                         | DSL                | Yes.        |
| Sulfonic acids, petroleum, calcium salts | DSL                | Yes.        |
| Propane                                  | DSL                | Yes.        |

## HMIS - Hazardous Materials Identification System

Health - 2      Flammability - 3      Physical Hazard - 1

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

## WHMIS Classification(s):

- Class A - Compressed Gas
- Class B5 - Flammable Aerosol
- Class D2B - Skin/Eye Irritant

## WHMIS Hazard Symbols:



## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.



# MATERIAL SAFETY DATA SHEET

## Squeak Relief™

**NTP (N)** National Toxicology Program.  
1 - Known to be carcinogens.  
2 - Reasonably anticipated to be carcinogens.

|                                      |
|--------------------------------------|
| <b>Section 16: OTHER INFORMATION</b> |
|--------------------------------------|

**Disclaimer:**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Canadian WHMIS Expiry Date:** February 5, 2012

**Version #:** 1.0

**Prepared by:** Nexreg Compliance Inc.  
(519) 488-5126  
[www.nexreg.com](http://www.nexreg.com)