



Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/11/2016

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Lucas Multi-Vehicle CVT Fluid :
Product code : 10111

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant
Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

Lucas Oil Products, Inc
302 North Sheridan Street
Corona, California 92880-2067 - USA
T (951) 270-0154 - F (951) 270-1902
GHewgill@lucasoil.com - www.LucasOil.com

1.4. Emergency telephone number

Emergency number : (951) 493-1149 (951) 847-5949 7:00A.M. to 5:00P.M. Monday thru Friday

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

2.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
2.41% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
2.41% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS No) 64742-54-7	30 – 50	Asp. Tox. 1, H304
Mineral oil	(CAS No) mixture	1 – 5	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic (DMSO < 3%)	(CAS No) 64742-55-8	1 – 5	Asp. Tox. 1, H304
Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.		0.1 – 1.5	Skin Sens. 1B, H317
bis(nonylphenyl)amine	(CAS No) 36878-20-3	0.1 – 1.5	Aquatic Chronic 4, H413
Dibutyl phosphite	(CAS No) 1809-19-4	0.1 – 1.5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Tris(2-ethylhexyl) orthoborate	(CAS No) trade secret	0.1 – 1.5	Eye Irrit. 2A, H319 Aquatic Chronic 4, H413
c14-18 alpha-olefin epoxide, reaction products with boric acid		< 0.5	Skin Sens. 1B, H317
1,2-Propanediol, 3-amino, N,N-dicoco alkyl derivs.		< 0.5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water spray.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flammable resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Do not eat, drink or smoke when using this product.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container closed when not in use.
Incompatible products	: Strong acids. Strong bases. Strong oxidizers.
Heat and ignition sources	: Keep away from heat, sparks and flame.
Prohibitions on mixed storage	: Incompatible materials.
Storage area	: Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Mineral oil (mixture)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.		
Not applicable		
bis(nonylphenyl)amine (36878-20-3)		
Not applicable		
Dibutyl phosphite (1809-19-4)		
Not applicable		
c14-18 alpha-olefin epoxide, reaction products with boric acid		
Not applicable		
1,2-Propanediol, 3-amino, N,N-dicoco alkyl derivs.		
Not applicable		
Tris(2-ethylhexyl) orthoborate (trade secret)		
Not applicable		
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls	: Avoid splashing. Ensure good ventilation of the work station. Emergency safety showers should be available in the immediate vicinity of any potential exposure.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves.
Eye protection	: In case of splashing or aerosol production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. NIOSH. Approved respirator.
Environmental exposure controls	: Prevent leakage or spillage.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available

Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 149.4 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 33.2 cSt @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO₂). Hydrocarbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 10.5 mg/l/4h
bis(nonylphenyl)amine (36878-20-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
1,2-Propanediol, 3-amino, N,N-dicoco alkyl derivs.	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
LD50 oral rat	> 5000 mg/kg

Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecotoxicological data about this product are known.

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)	
LC50 fish 1	101 mg/l > 100 mg/l LL50. 101 is put in for calculations, per request of IPAC

bis(nonylphenyl)amine (36878-20-3)	
LC50 fish 1	> 100 mg/l

Dibutyl phosphite (1809-19-4)	
LC50 fish 1	63.4 mg/l 96 h
EC50 Daphnia 1	20.8 mg/l 48 h

1,2-Propanediol, 3-amino, N,N-dicoco alkyl derivs.	
LC50 fish 1	> 100 mg/l 96 h
EC50 Daphnia 1	230 mg/l 48 h

Tris(2-ethylhexyl) orthoborate (trade secret)	
LC50 fish 1	21.17 mg/l 96 h

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
EC50 Daphnia 1	> 10000 mg/l

12.2. Persistence and degradability

Lucas Multi-Vehicle CVT Fluid	
Persistence and degradability	Not established.

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)	
Persistence and degradability	Not readily biodegradable.

1,2-Propanediol, 3-amino, N,N-dicoco alkyl derivs.	
Biodegradation	11 % 28 d

12.3. Bioaccumulative potential

Lucas Multi-Vehicle CVT Fluid	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Lucas Multi-Vehicle CVT Fluid	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Other information : No additional information available.

Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

TDG

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List) inventory

bis(nonylphenyl)amine (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List) inventory

Dibutyl phosphite (1809-19-4)

Listed on the Canadian DSL (Domestic Substances List) inventory

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List) inventory

National regulations

Lucas Multi-Vehicle CVT Fluid

All ingredients are listed in the Domestic Substances List (DSL)

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on Taiwan National Chemical Inventory

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

bis(nonylphenyl)amine (36878-20-3)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on Taiwan National Chemical Inventory

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Lucas Multi-Vehicle CVT Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists).
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.


Full text of H-statements:

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



SDS Prepared by:

The Redstone Group, LLC
6077 Frantz Rd
Suite 206
Dublin, Ohio USA 43016
614.923.7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product