OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Plews Kit #: 15162, 15163, 15164, 15189, 15282, 15298

### 1 Identification

- · Product identifier Plews 12077, 13230, 14130, 14132, 14134
- · Trade name: Non-Flammable Rubber Cement
- · Details of the supplier of the safety data sheet
- · Distributor:

Plews & Edelmann 1550 Franklin Grove Rd.

Dixon, IL 61021 Ph: 800-545-1689

· Emergency telephone number:

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300 or Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## 2 Hazard(s) identification

### · Classification of the substance or mixture



### GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.	
Carc. 1B H350 May cause cancer.	
Repr. 1A H360 May damage fertility or the unborn child.	
STOT RE 2 H373 May cause damage to organs through prolonged or repeate	ed exposure.



## GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetylene Trichloride (Trichloroethylene ) methylene chloride

Hazard statements

Causes skin irritation.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014

### 1 Identification

· Product identifier: Plews 15161, 15165, 15184, 15206, 15207, 15280, 15281

· Trade name: Tire Repair String

· Details of the supplier of the safety data sheet

· Supplier:

Plews & edelmann

1550 Franklin Grove Road

Dixon. Illinois 61021 Phone: 800-545-1689

Emergency telephone number:

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300 or Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## Hazard(s) identification

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Non-Regulated Material
- · Hazard pictograms Non-Regulated Material
- · Signal word Non-Regulated Material
- · Hazard statements Non-Regulated Material
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 0

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture: consisting of non-regulated material.
- Dangerous Components: Non-Regulated Material

### 4 First-aid measures

- Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Hold eyelids apart and flush eyes with plenty of water for at least 20 minutes.

Seek medical treatment.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014

Trade name: Tire Repair String

(Contd. of page 1)

· After swallowing:

Seek immediate medical advice.

Do not induce vomiting without medical advice.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
  No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

May produce incomplete combustion products (CO, CO<sub>2</sub>).

- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Use the appropriate tools to collect the material and dispose of it in an approved waste diposal container.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014

Trade name: Tire Repair String

(Contd. of page 2)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not applicable.
- · Eye protection: Not required.

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid

Color:
Odor:
Odor threshold:
No data available
No data available
Not determined.

PH-value:
Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Not determined.
Not applicable.
Not applicable.
Not determined.
Not applicable.
Not determined.
Not determined.
Not determined.
Not determined.
Not determined.

· **Auto igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

**Lower:** 1.1 Vol % **Upper:** 12.5 Vol %

· Vapor pressure @ 20 °C (68 °F): 3300 hPa (2475 mm Hg)

· Density:

Relative densityNot determined.Vapour densityNot applicable.Evaporation rateNot applicable.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not applicable. **Kinematic:** Not applicable.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014

Trade name: Tire Repair String

(Contd. of page 3)

· Solvent content:

Organic solvents: 0.0 %
Solids content: 100.0 %

· Other information No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

Carbon dioxide and carbon monoxide may form when heated to decomposition

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritating effect.
- · on the eye: No irritating effect.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

#### NTP (National Toxicology Program)

None of the ingredients are listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014

Trade name: Tire Repair String

(Contd. of page 4)

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

Smaller quantities can be disposed of with household waste.

Recycle or dipose with household trash.

- Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

### \*14 Transport information

· UN-Number

· **DOT, ADR, ADN, IMDG, IATA**Non-Regulated Material

· UN proper shipping name

DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

· Packing group

DOT, ADR, IMDG, IATA Non-Regulated Material

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014

Trade name: Tire Repair String

(Contd. of page 5)

· Chemica	Is known to cause reproductive toxicity for males:
None of t	ne ingredients are listed.
· Chemica	ls known to cause developmental toxicity:
None of the	ne ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

- GHS label elements Non-Regulated Material
- · Hazard pictograms Non-Regulated Material
- · Signal word Non-Regulated Material
- · Hazard statements Non-Regulated Material
- · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know

32131-17-2 Hexamethylenediamine

9010-85-9 Butyl Rubber

All ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

#### Trade name: Non-Flammable Rubber Cement

(Contd. of page 1)

Causes serious eye irritation.

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

### · Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1 Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = \*2 Fire = 1

Reactivity = 0

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture: consisting of the following components.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 2)

· Dangerou	s Components:	
79-01-6	Acetylene Trichloride (Trichloroethylene )  Muta. 2, H341; Carc. 1B, H350; Repr. 1A, H360; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336; Aquatic Chronic 3, H412	45-55%
75-09-2	methylene chloride	35-45%
9006-04-6	Natural rubber latex	5-15%
· <b>SVHC</b> 79-01-6 A	cetylene Trichloride (Trichloroethylene )	

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Not a normal route of entry.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Wash with soap and water.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Not anticipated under normal use.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Use the appropriate tools to collect the material and dispose of it in an approved waste diposal container.

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 3)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

#### · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep protective respiratory device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with occupational exposure limits:	
79-01	l-6 Acetylene Trichloride (Trichloroethylene )
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 2 hrs
REL	See Pocket Guide Apps. A and C
TLV	Short-term value: 135 mg/m³, 25 ppm Long-term value: 54 mg/m³, 10 ppm BEI
75-09	9-2 methylene chloride
PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m³, 50 ppm BEI
9006	-04-6 Natural rubber latex
TLV	Long-term value: 0.0001* mg/m³ Skin; DSEN, RSEN;* inh. fraction

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 4)

### · Ingredients with biological limit values:

### 79-01-6 Acetylene Trichloride (Trichloroethylene )

BEI 15 ma/L

urine

end of shift at end of workweek

Trichloroacetic acid (nonspecific)

0.5 mg/L

blood

end of shift at end of workweek

Trichloroethanol without hydrolysis (nonspecific)

-

blood

end of shift at end of workweek

Trichloroethylene (semi-quantitative)

\_

end-exhaled air

end of shift at end of workweek

Trichloroethylene (semi-quantitative)

### 75-09-2 methylene chloride

BEI 0.3 mg/L

urine

end of shift

Dichloromethane (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 5)

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection: Safety glasses

Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Color:
Color:
Color:
Chloroform-like
Codor threshold:
Not determined.

Pasty
Light yellow
Chloroform-like
Not determined.

· Change in condition

Melting point/Melting range: Not determined.
Boiling point/Boiling range: 40 °C (104 °F)

• *Flash point:* > 410 °C (> 770 °F)

Flammability (solid, gaseous): Not applicable.
 Ignition temperature: 410 °C (770 °F)
 Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

 Lower:
 7.9 Vol %

 Upper:
 90.0 Vol %

· Vapor pressure @ 20 °C (68 °F): 453 hPa (340 mm Hg)

• **Density @ 20 °C (68 °F):** 1.362 g/cm³ (11.366 lbs/gal)

Relative densityVapour densityEvaporation rateNot determined.Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 90.0 % VOC content: 45-50 %

· Other information No further relevant information available.

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 6)

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided:

Carbon dioxide and carbon monoxide may form when heated to decomposition

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flame and ignition sources.
- Incompatible materials: Strong oxidizing agents.
- Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
79-01-6 Acetylene Trichloride (Trichloroethylene )			
Oral	LD50	2402 mg/kg (mouse)	
Dermal	LD50	8450 mg/kg (mouse)	
75-09-2 methylene		chloride	
Oral	LD50	1600 mg/kg (rat)	
Inhalative	LC50/4 h	88 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye:

Irritating effect.

Causes serious eye irritation.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

79-01-6 Acetylene Trichloride (Trichloroethylene )	2A
75-09-2 methylene chloride	2B
· NTP (National Toxicology Program)	
79-01-6 Acetylene Trichloride (Trichloroethylene )	R
75-09-2 methylene chloride	R
OSHA-Ca (Occupational Safety & Health Administration)	
75-09-2 methylene chloride	

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 7)

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## \*13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

· Packing group

· **DOT, ADR, IMDG, IATA** Non-Regulated Material

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

Trade name: Non-Flammable Rubber Cement

(Contd. of page 8)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section	355 (extremely hazardous substances):
None of	the ingredients are listed.
· Section	313 (Specific toxic chemical listings):
79-01-6	Acetylene Trichloride (Trichloroethylene )
75-09-2	methylene chloride
· TSCA (	Toxic Substances Control Act):
79-01-6	Acetylene Trichloride (Trichloroethylene )
75-09-2	methylene chloride

Proposition 65

1 Toposition 00		
· Chemicals known to cause cancer:		
79-01-6 Acetylene Trichloride (Trichloroethylene )		
75-09-2 methylene chloride		
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients are listed.		
· Chemicals known to cause reproductive toxicity for males:		
79-01-6 Acetylene Trichloride (Trichloroethylene )		
· Chemicals known to cause developmental toxicity:		

Carcinogenic categories

79-01-6 Acetylene Trichloride (Trichloroethylene )

EPA (Environmental Protection Agency)	
79-01-6 Acetylene Trichloride (Trichloroethylene )	СаН
75-09-2 methylene chloride	L
TLV (Threshold Limit Value established by ACGIH)	
79-01-6 Acetylene Trichloride (Trichloroethylene )	A2
75-09-2 methylene chloride	A3
NIOSH-Ca (National Institute for Occupational Safety and Health)	
79-01-6 Acetylene Trichloride (Trichloroethylene )	
75-09-2 methylene chloride	

### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Danger
- · *Hazard-determining components of labeling:* Acetylene Trichloride (Trichloroethylene )

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing date 11/25/2014 Reviewed on 11/25/2014

#### Trade name: Non-Flammable Rubber Cement

(Contd. of page 9)

methylene chloride

### Hazard statements

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

### · Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

#### State Right to Know

79-01-6 Acetylene Trichloride (Trichloroethylene )

Muta. 2, H341; Carc. 1B, H350; Repr. 1A, H360; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336; Aquatic Chronic 3, H412

75-09-2 methylene chloride

♦ Carc. 2, H351; STOT RE 2, H373; ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335-H336

9006-04-6 Natural rubber latex

All ingredients are listed.

- · Information about limitation of use:
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/25/2014 Printing date 11/25/2014

#### Trade name: Non-Flammable Rubber Cement

(Contd. of page 10)

establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### · Date of preparation / last revision 11/25/2014 / -

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Muta. 2: Germ cell mutagenicity, Hazard Category 2

Carc. 1B: Carcinogenicity, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 1A: Reproductive toxicity, Hazard Category 1A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

\* Data compared to the previous version altered.