

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/12/2014

Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : NGEN OIL SYSTEM CLEANER 16 FL.OZ.
Product code : 71016

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Oil System Cleaner

1.3. Details of the supplier of the safety data sheet

The Next Generation Manufacturing, LLC
423 W. WESLEY
Wheaton, IL 60187
T 844-643-6776

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: H227 - Combustible liquid
H315 - Causes skin irritation
H319 - Causes serious eye irritation

Precautionary statements (GHS-US)

: P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P264 - Wash affected areas thoroughly after handling
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P302+P352 - If on skin: Wash with plenty of soap and water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P321 - Specific treatment: See section 4.1 on this label
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
distillates (petroleum), hydrotreated heavy naphthenic	(CAS No) 64742-52-5	85 - 95	Not classified
2-butoxyethanol	(CAS No) 111-76-2	10 - 30	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Respiratory arrest: artificial respiration or oxygen. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.
- First-aid measures after skin contact : Take victim to a doctor if irritation persists. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible. Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : On burning: release of irritant gases/vapours (carbon monoxide - carbon dioxide). May form peroxides.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Protective equipment : Protective clothing. Protective goggles. Gloves. Face-shield.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Plug the leak, cut off the supply. Contain released substance, pump into suitable containers. Dam up the liquid spill.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
- Precautions for safe handling : Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Eliminate all ignition sources if safe to do so. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.
- Incompatible products : Oxidizing agent. Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (mg/m³)	97 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH STEL (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ MIST 8 HOURS
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ MIST 8 HOURS

8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Protective clothing. Wear suitable protective clothing.
- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Yellow liquid.
- Color : Light yellow.
- Odor : Ether-like odour. Sweet.
- Odor threshold : No data available
- pH : NA
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : NA
- Flash point : 66 °C Closed Cup

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: NA
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: NA
Relative vapor density at 20 °C	: No data available
Relative density	: 0.89
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: NA
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 15 %

SECTION 10: Stability and reactivity

10.1. Reactivity

On burning: release of irritant gases/vapours (carbon monoxide - carbon dioxide). May form peroxides.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

NGEN OIL SYSTEM CLEANER 16 FL.OZ.	
LD50 oral rat	> 15 mg/kg
LC50 inhalation rat (ppm)	450 ppm/4h

2-butoxyethanol (111-76-2)	
LD50 oral rat	530 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 1746 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value, 435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486, Rat; Weight of evidence

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

pH: NA

Serious eye damage/irritation : Causes serious eye irritation.

pH: NA

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classifiedBased on available data, the classification criteria are not met

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified

2-butoxyethanol (111-76-2)	
IARC group	3

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
IARC group	3

Reproductive toxicity : Not classifiedBased on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classifiedBased on available data, the classification criteria are not met

Aspiration hazard : Not classifiedBased on available data, the classification criteria are not met

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

2-butoxyethanol (111-76-2)	
LC50 fish 1	116 ppm (96 h; Cyprinodon variegatus; Nominal concentration)
EC50 Daphnia 1	1700 mg/l (48 h; Daphnia sp.; Nominal concentration)
LC50 fish 2	1341 ppm (96 h; Lepomis macrochirus)
EC50 Daphnia 2	1720 mg/l (24 h; Daphnia magna)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	900 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	35 mg/l (192 h; Microcystis aeruginosa)

12.2. Persistence and degradability

NGEN OIL SYSTEM CLEANER 16 FL.OZ.	
Persistence and degradability	Not established.

2-butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.20 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31 % ThOD

12.3. Bioaccumulative potential

NGEN OIL SYSTEM CLEANER 16 FL.OZ.	
Bioaccumulative potential	Not established.

2-butoxyethanol (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

2-butoxyethanol (111-76-2)	
Surface tension	0.027 N/m (25 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): NA1993, Combustible liquid, n.o.s. (2-butoxyethanol, Petroleum Distillates), 3, III, Limited Quantity

ICAO/IATA (air): Not Regulated,

IMO/IMDG (water): Not Regulated,

Special Provisions: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

14.2. UN proper shipping name

DOT Proper Shipping Name : Combustible liquid, n.o.s. (2-butoxyethanol, Petroleum Distillates)

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

NGEN OIL SYSTEM CLEANER 16 FL.OZ.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

NGEN OIL SYSTEM CLEANER 16 FL.OZ.	
WHMIS Classification	Class B Division 3 - Combustible Liquid

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.2; R45

T+; R28

Full text of R-phrases: see section 16

15.2.2. National regulations

No additional information available

15.3. US State regulations

NGEN OIL SYSTEM CLEANER 16 FL.OZ.()	
State or local regulations	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

2-butoxyethanol (111-76-2)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

NGEN OIL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012) - Technical Chemical

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.