

# SAFETY DATA SHEET

Revision Date 25-Jan-2018 Version 3

# 1. IDENTIFICATION

**Product identifier** 

Product Name Full Throttle GDI+ Intake & Induction Cleaner

Other means of identification

Product Code FT3000 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Uses advised against All other applications

Details of the supplier of the safety data sheet

<u>Supplier Address</u> <u>Manufacturer Address</u> <u>Manufactured and Distributed by:</u>

ITW Professional Automotive Products

3606 Craftsman Blvd. Lakeland, FL 33803

<u>Distributor</u> <u>May Also Be Distributed by:</u>

Logistic Distribution 550 Industrial Drive

Milton, ON, Canada L9T 5A6

Company Phone Number 863-665-3338

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003583

E-mail address EHS@itwproap.com

# 2. HAZARDS IDENTIFICATION

# Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### NOTE:

Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 1

# Label elements

**Emergency Overview** 

# Signal word

### Danger

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May damage fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable liquid and vapor



Appearance Clear

Physical state Liquid

Odor Strong solvent odor.

# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use non-sparking tools

Take precautionary measures against static discharge

Keep cool

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

- Toxic to aquatic life with long lasting effects

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
N-Methylpyrrolidone	872-50-4	10 - 30	*
Xylene	1330-20-7	10 - 30	*
Solvent naphtha (petroleum), medium aliph.	64742-88-7	10 - 30	*
Ethylbenzene	100-41-4	7 - 13	*
Solvent naphtha (petroleum), light aliph.	64742-89-8	3 - 7	*

# 4. FIRST AID MEASURES

### **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Use personal protective equipment as required.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m <sup>3</sup>	_

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state Liquid Appearance Clear

**Odor** Strong solvent odor.

**Color** amber

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point 11 °C / 52 °F
Evaporation rate
Flammability (solid, gas)
No information available
No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Relative density 0.86

Water solubility
Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available

Kinematic viscosity 2 mm2/s

Dynamic viscosity

Explosive properties

Oxidizing properties

No information available
No information available
No information available

**Other Information** 

Softening point No information available Molecular weight No information available

**VOC Content (%)** 69.56

DensityNo information availableBulk densityNo information available

#### 10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

#### Chemical stability

Stable under recommended storage conditions

### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Excessive heat.

### Incompatible materials

Strong oxidizing agents

# **Hazardous Decomposition Products**

Carbon oxides

### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
N-Methylpyrrolidone 872-50-4	= 3914 mg/kg (Rat)	= 8 g/kg(Rabbit)	= 3.1 mg/L (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg(Rat)	> 4350 mg/kg (Rabbit)> 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h = 5000 ppm (Rat)4 h
Solvent naphtha (petroleum), medium aliph. 64742-88-7	> 5000 mg/kg(Rat)	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L (Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg(Rat)	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L (Rat)4 h
Solvent naphtha (petroleum), light aliph. 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-

### Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene	-	Group 3	-	-
1330-20-7				
Ethylbenzene	A3	Group 2B	-	X
100-41-4		,		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Target Organ Effects** Central nervous system, Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5706 mg/kg
ATEmix (dermal) 3059 mg/kg
ATEmix (inhalation-gas) 6944 mg/l
ATEmix (inhalation-dust/mist) 3.9 mg/l

# 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

## **Ecotoxicity**

0.56 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### Mobility

No information available.

Chemical Name	Partition coefficient
N-Methylpyrrolidone	-0.46
872-50-4	
Xylene	2.77 - 3.15
1330-20-7	
Ethylbenzene	3.118
100-41-4	

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

**Contaminated packaging** Do not reuse container.

US EPA Waste Number D001, U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethylbenzene	Toxic
100-41-4	Ignitable

# 14. TRANSPORT INFORMATION

NOTE:

DOT

UN/ID no UN1993

Proper shipping name: Flammable liquids, n.o.s, (contains xylene and isopropanol), Limited Quantity (LQ)

Hazard Class 3 Packing Group II

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

**IATA** 

UN/ID no UN1993

Proper shipping name: Flammable liquid, n.o.s, (Contains xylene and isopropanol), Limited Quantity (LQ)

Hazard Class 3
Packing Group II

**IMDG** 

UN/ID no UN1993

Proper shipping name: Flammable liquids, n.o.s, (Contains xylene and isopropanol), Limited Quantity (LQ)

Hazard Class 3
Packing Group ||

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Complies Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	1.0
N-Methylpyrrolidone - 872-50-4	1.0
Xylene - 1330-20-7	1.0
Ethylbenzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb	-	-	Х

1330-20-7				
Ethylbenzene	1000 lb	X	X	X
100-41-4				

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

#### **US State Regulations**

### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
N-Methylpyrrolidone - 872-50-4	Developmental
Ethylbenzene - 100-41-4	Carcinogen

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Isopropanol 67-63-0	Х	X	X
N-Methylpyrrolidone 872-50-4	Х	X	X
Xylene 1330-20-7	Х	X	X
Solvent naphtha (petroleum), medium aliph. 64742-88-7	X	-	-
Ethylbenzene 100-41-4	Х	X	Х
Deionized Water 7732-18-5	-	-	Х
Ammonium Hydroxide 1336-21-6	Х	Х	Х

### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

### **WHMIS Hazard Class**

B2 - Flammable liquid, D2A - Very toxic materials, D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 4 Instability 0 HMIS Health hazards 2 Flammability 4 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 25-Jan-2018

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**