

SECTION 1: PRODUCT IDENTIFICATION

Product: Sting Relief Pad

Product Label Name: Sting Relief Pad

Company Name and Address: Dukal Corporation
2 Fleetwood Court
Ronkonkoma, NY 11779

Emergency Telephone Number: 631-656-3800

SECTION 2: HAZARDOUS IDENTIFICATION

Hazard Class/Category: Flammable Liquid – 3
Eye Irritation – 2B

Hazard Symbol:



Signal Word: Warning

Hazard Statements: Flammable liquid and vapor. (H226)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)

Precautionary statements:

General: Keep out of reach of children. (P102)

Eyes: IF IN EYES: Rinse cautiously with water for several minutes.
If eye irritation persists: Get medical advice/attention.
(P305+P338) (P337+P313)

Respiratory: None

SECTION 3: INFORMATION ON INGREDIENTS

Component Name	CAS #	Concentration	R Phrase
Isopropyl Alcohol	67-63-0	60%	R11
Benzocaine	94-09-7	6%	

Chemical Formula: NH₂C₆H₄COOC₂H₅ / CH₃CHOHCH₃



SAFETY DATA SHEET

SECTION 4: FIRST-AID MEASURES

Emergency first aid procedures by route of exposure:

Inhalation: If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion: Do not induce vomiting. If the material is swallowed have victim drink 1-3 glasses of water to dilute stomach contents. Seek medical attention or advice.

Skin: If irritation is experienced, discontinue use. If irritation persists, seek medical attention.

Eyes: Rinse eyes with cool water for 15 minutes holding the eye open. Seek medical attention if irritation persists

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: 68.5°F, TOC Method

Flammable Limits: 750°F

Extinguishing Media: Use methods appropriate for the surrounding fire. Suggested: CO2, dry chemical powder, or alcohol resistant foam.

Products of Combustion: Upon decomposition this product may emit carbon dioxide, carbon monoxide and/or low molecular weight hydrocarbons.

Fire Fighting Equipment/Instructions: Wear protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and self contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: For large spills wear gloves, safety glasses and when levels exceed OSHA PEL use appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

Environmental Precautions: Prevent discharge to open waters.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

Methods for Clean-Up: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container. Wash spill area with water.



SAFETY DATA SHEET

SECTION 7: HANDLING AND STORAGE

Handling: Keep away from heat, sparks and flame. Prevent contact with eyes. Use in well ventilated area.

Storage: Keep the container tightly closed and in a cool, well ventilated place.

SECTION 8: EXPOSURE CONTROLS

Isopropyl Alcohol (67-63-0)

ACGIH OEL: 200 ppm TWA

OSHA OEL: 400 ppm TWA; 980 mg/m³ TWA

Engineering Controls: Normal room ventilation is usually adequate under normal use.

Personal Protective Equipment (PPE):

Eye/Face Protection: None needed under normal use – Wear goggles if exposed to unusual amount and splashing

Skin Protection: None needed under normal use -- Wear overalls or apron if splashing is possible

Respiratory Protection: May be needed if vapor concentrations are high.

General Hygiene Considerations: None needed under normal use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Individually sealed Sting Relief Packet. Packet may contain some free liquid.

Appearance/Color: White Non-Woven cloth saturated with clear solution

Odor: Alcohol

PH: Not Available.

Vapor Pressure: Not Available.

Flammability Properties (see section 5)

Solubility (in water): Chemical Is Soluble, Pad Not Soluble

Specific Gravity @ 25°C: 0.8405

Evaporation Rate: Not Available

Auto-ignition temperature: Not Available

Decomposition temperature: Not Available



SAFETY DATA SHEET

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under normal ambient temperatures 70°C (21°C)

Condition to Avoid: Avoid excessive heat or sources of ignition.

Incompatible Materials: This product reacts with strong acid, strong bases, and oxidizing agents.

Hazardous Decomposition: Not Available.

Hazardous Reactions: Hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

A: General Product information

Product contains isopropyl alcohol.

B: Acute Toxicity

Low order of acute toxicity is possible.

CHRONIC EFFECTS: Component

Isopropyl Alcohol (67-63-0) -- This product is not expected to cause long term adverse effects

Carcinogenicity: Not Classifiable as a Human Carcinogen

Reproductive: This product is not expected to cause reproductive health effects

Developmental: This product is not expected to cause reproductive health effects.

Target Organs: When consumed, isopropyl alcohol can target the respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

SECTION 12: ECOLOGICAL INFORMATION

Mixtures of alcohols are toxic to aquatic life at moderate to low concentrations. No long-term ecological effects are likely. Concentrated solutions of alcohols and surfactants may cause damage to aquatic and terrestrial plants.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with federal state and local regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld near container. Do not incinerate closed containers. Empty containers may contain hazardous residues. Dispose of containers with care.

SECTION 14: TRANSPORTATION INFORMATION

DOT

Not Regulated as Hazardous Material under DOT 49 CFR 172.102 Special Provision 47

Proper Shipping Name

Solids containing Flammable Liquid. n.o.s. (Isopropanol)

Hazard Class

4.1

Packing Group

II

Description

Solids Containing Flammable Liquid n.o.s. (Isopropanol)

UN#

UN3175



SAFETY DATA SHEET

UN-No.	UN3175
Proper Shipping Name	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)

IATA	Not Regulated as Hazardous Material under IATA Sec. 4.4 Special Provision A46
-------------	--

UN-No.	UN3175
Proper Shipping Name	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Marine Pollutant	No

IMDG/IMO	Not Regulated as Hazardous Material under IMDG Ch. 3.3 Special Provision 216
-----------------	---

UN-No.	UN3175
Proper Shipping Name	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Marine Pollutant	No

DOT/IATA/IMDG Special Provisions: (DOT) Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, for single packaging, each packaging must correspond to a design type that has passed a leak-proof test at the Packing Group II level. Small inner packaging consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to this subchapter provided there is no free liquid in the packet or article. (IATA) Small inner packaging consisting of sealed packets or articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Regulations provided there is no free liquid in the packet or article. (IMDG) Sealed packets containing 10 ml or less of Class 3 flammable liquids in Packing Group II or III which are absorbed into a solid with no free liquid at the time of shipment are not regulated.

SECTION 15: REGULATORY INFORMATION

DOT / USA	
Product Description:	Solid Containing Flammable Liquid n.o.s. (Isopropanol)



SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION

Issue Date: 03-26-2014
Revision Date: 04-15-2017

Disclaimer:

The information provided in this SDS is correct and is to the best of our knowledge, at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.