

SAFETY DATA SHEET

Issuing Date 01-Jun-2015

Revision Date 01-Jun-2015

Revision Number 4



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier 50205MB
Product Name Mechanics Brand Engine Degreaser

Recommended Use Engine Degreaser - Aerosol

Details of the supplier of the safety data sheet

Supplier Name Airosol Company, Inc.

Supplier Address P.O. Box 120
1206 Illinois St.
Neodesha
KS
66757
US

Supplier Phone Number Phone:620-325-2666

Emergency telephone number 1-800-535-5053

Company Emergency Phone Number 1-800-633-9576

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2



Flammable Aerosols

Category 2

GHS Label elements, including precautionary statements**Emergency Overview**

Signal word	Danger
Hazard Statements Causes skin irritation Causes serious eye damage Suspected of causing cancer Flammable aerosol	
	
Appearance White	Physical state Liquid spray Aerosol
	Odor Naphthalenic

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Pressurized container: Do not pierce or burn, even after use
 Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

13.75% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Naphtha (petroleum), heavy aromatic	64742-94-5	10 - 30
Dipropylene glycol monomethyl ether	34590-94-8	10 - 30
Oleic acid	112-80-1	10 - 30
Propane	74-98-6	3 - 7
Butane	106-97-8	3 - 7
Potassium hydroxide	1310-58-3	1 - 5
Triethanolamine	102-71-6	1 - 5
Diethanolamine	111-42-2	0.1 - 1

4. FIRST AID MEASURES**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical attention/advice.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Uniform Fire Code

Irritant: Liquid
Aerosols: Level III

Explosion Data

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges.

Other Information Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Refer to protective measures listed in Sections 7 and 8. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Use only with adequate ventilation and in closed systems. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Do not stick pin or any other sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Dipropylene glycol monomethyl ether 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m ³ (vacated) S* S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Triethanolamine 102-71-6	TWA: 5 mg/m ³	-	
Diethanolamine 111-42-2	TWA: 1 mg/m ³ inhalable fraction and vapor S*	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m ³	TWA: 3 ppm TWA: 15 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid spray, Aerosol	Odor	Naphthalenic
Appearance	White	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	1.01	None known	
Water Solubility	Soluble in water	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. (based on components). Causes serious eye damage. Severely irritating to eyes. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Dipropylene glycol monomethyl ether 34590-94-8	= 5230 mg/kg (Rat)	= 9500 mg/kg (Rabbit)	-
Oleic acid 112-80-1	> 5000 mg/kg (Rat)	-	-
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Potassium hydroxide 1310-58-3	= 214 mg/kg (Rat)	-	-
Triethanolamine 102-71-6	= 4190 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-

Information on toxicological effects

Symptoms	Erythema (skin redness). May cause redness and tearing of the eyes. May cause blindness. Burning.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Triethanolamine 102-71-6		Group 3		
Diethanolamine 111-42-2	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	No information available.
------------------------------	---------------------------



STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	Contains a known or suspected carcinogen.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Nervous System (CNS).
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

6,697.00 mg/kg

ATEmix (dermal)

56,122.00 mg/kg (ATE)

ATEmix (inhalation-gas)

2,715,191.50

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Naphtha (petroleum), heavy aromatic 64742-94-5	72h EC50: = 2.5 mg/L (Skeletonema costatum)	96h LC50: = 19 mg/L (Pimephales promelas) 96h LC50: = 2.34 mg/L (Oncorhynchus mykiss) 96h LC50: = 1740 mg/L (Lepomis macrochirus) 96h LC50: = 45 mg/L (Pimephales promelas) 96h LC50: = 41 mg/L (Pimephales promelas)		48h EC50: = 0.95 mg/L
Dipropylene glycol monomethyl ether 34590-94-8		96h LC50: > 10000 mg/L (Pimephales promelas)		48h LC50: = 1919 mg/L
Oleic acid 112-80-1		96h LC50: = 205 mg/L (Pimephales promelas)		
Potassium hydroxide 1310-58-3		96h LC50: = 80 mg/L (Gambusia affinis)		
Triethanolamine 102-71-6	96h EC50: = 169 mg/L (Desmodesmus subspicatus) 72h EC50: = 216 mg/L (Desmodesmus subspicatus)	96h LC50: 10600 - 13000 mg/L (Pimephales promelas) 96h LC50: > 1000 mg/L (Pimephales promelas) 96h LC50: 450 - 1000 mg/L (Lepomis macrochirus)		24h EC50: = 1386 mg/L
Diethanolamine 111-42-2	72h EC50: = 7.8 mg/L (Desmodesmus subspicatus) 96h EC50: 2.1 - 2.3 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 4460 - 4980 mg/L (Pimephales promelas) 96h LC50: 1200 - 1580 mg/L (Pimephales promelas) 96h LC50: 600 - 1000 mg/L (Lepomis macrochirus)		48h EC50: = 55 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Naphtha (petroleum), heavy aromatic 64742-94-5	6.1
Dipropylene glycol monomethyl ether 34590-94-8	-0.064
Propane 74-98-6	2.3
Butane 106-97-8	2.89
Potassium hydroxide 1310-58-3	0.83
Triethanolamine 102-71-6	-2.53
Diethanolamine 111-42-2	-2.18

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Potassium hydroxide 1310-58-3	Toxic Corrosive

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name	CONSUMER COMMODITY
Hazard Class	2.1
Description	CONSUMER COMMODITY, ORM-D
Emergency Response Guide Number	126

TDG

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

MEX

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950 AEROSOLS, 2.1,

ICAO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

IATA

UN-No.	UN1950
Proper Shipping Name	AEROSOLS, FLAMMABLE
Hazard Class	2.1
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1

IMDG/IMO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
EmS-No.	F-D, S-U



Description UN1950, AEROSOLS, 2.1

RID

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Classification code 5F
 Description UN1950 AEROSOLS, 2.1,

ADR

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Classification code 5F
 Tunnel restriction code (D)
 Description UN1950 AEROSOLS, 2.1,

ADN

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Classification code 5F
 Special Provisions 190, 327, 625
 Description UN1950 AEROSOLS, 2.1,
 Hazard Labels 2.1
 Limited Quantity LQ2
 Ventilation VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Diethanolamine - 111-42-2	111-42-2	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
 Chronic Health Hazard Yes
 Fire Hazard Yes
 Sudden release of pressure hazard Yes
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
---------------	-----------------------------	------------------------	---------------------------	----------------------------



Potassium hydroxide 1310-58-3	1000 lb			X
----------------------------------	---------	--	--	---

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Diethanolamine 111-42-2	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Diethanolamine - 111-42-2	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Dipropylene glycol monomethyl ether 34590-94-8	X	X	X	X	X
Oleic acid 112-80-1			X		
Butane 106-97-8	X	X	X		
Propane 74-98-6	X	X	X		
Potassium hydroxide 1310-58-3	X	X	X	X	
Triethanolamine 102-71-6	X	X	X		
Diethanolamine 111-42-2	X	X	X	X	X

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Dipropylene glycol monomethyl ether 34590-94-8 (10 - 30)		Mexico: TWA 100 ppm Mexico: TWA 60 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 900 mg/m ³
Butane 106-97-8 (3 - 7)		Mexico: TWA 800 ppm Mexico: TWA 1900 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 3 *	Flammability 3	Physical Hazard 0	Personal Protection



X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	01-Jun-2015
Revision Date	01-Jun-2015, 11/17/2015
Revision Note	No information available

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

