



SAFETY DATA SHEET

Revision Date 18-Jul-2017

Version 3

1. IDENTIFICATION

Product identifier

Product Name WHITE LITHIUM GREASE 10.75OZ AE

Other means of identification

Product Code 81981

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Flammable Aerosol, Lubricant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

May Also Be Distributed by:

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Signal word

Danger

May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated

**Appearance** White**Physical state** Liquid Flammable Aerosol**Odor** Solvent**Precautionary Statements - Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Note L: The classification as a carcinogen 1 does not apply. The substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC	64741-96-4	5-25	*
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	5-25	*
PROPANE	74-98-6	10 - 30	*
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10 - 30	*
HEPTANE	142-82-5	5 - 10	*

4. FIRST AID MEASURES

Description of first aid measures**General advice**

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation persists, call a physician. Wash contaminated clothing

before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting. Rinse mouth.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed**Symptoms**

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed**Note to physicians**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Contains gas under pressure; may explode if heated. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal precautions**

Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Remove all sources of ignition. Do not puncture or incinerate cans.

Other Information

Ventilate the area.

Environmental precautions**Environmental precautions**

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling**Advice on safe handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Take precautionary measures against static discharges. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store locked up.

Incompatible materials

Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
HEPTANE 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls**Engineering Controls**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state
Appearance
Odor

Liquid; Flammable Aerosol
White
Solvent

Odor threshold No information available

Property**Values****Remarks • Method**

pH

No information available

Melting point / freezing point

No information available

Boiling point / boiling range

> 38 °C / >100 °F

Flash point

< -18 °C / < 0 °F

Gives a flame projection at full valve opening or flashback at any degree of valve opening

Evaporation rate

No information available

Flammability (solid, gas)

No information available

Flammability Limit in Air

Upper flammability limit:

No information available

Lower flammability limit:

No information available

Vapor pressure

No information available

Vapor density

>1

Air = 1

Relative density

0.905-0.915

Water solubility

Negligible

Solubility in other solvents

No information available

Partition coefficient

No information available

Autoignition temperature

No information available

Decomposition temperature

No information available

Kinematic viscosity

No information available

Dynamic viscosity

No information available

Explosive properties

No information available

Oxidizing properties

No information available

Other Information

Softening point

No information available

Molecular weight

No information available

VOC Content (%)

24.5%

Density

No information available

Bulk density

No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact Harmful in contact with skin. Prolonged contact may cause redness and irritation.

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
PROPANE 74-98-6	-	-	= 658 mg/L (Rat) 4 h
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
HEPTANE 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	A2	Group 1	Known	X
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 23833 mg/kg

ATEmix (dermal) 8006 mg/kg

ATEmix (inhalation-gas) 1824461 mg/l

ATEmix (inhalation-dust/mist) 1373 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

20 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
PROPANE 74-98-6	2.3
HEPTANE 142-82-5	4.66

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
HEPTANE 142-82-5	Toxic Ignitable

14. TRANSPORT INFORMATION**DOT**

UN/ID no	1950
Proper shipping name:	Aerosols, Limited Quantity (LQ)
Hazard Class	2.1
Emergency Response Guide Number	126

IATA

UN/ID no	ID 8000
Proper shipping name:	Consumer commodity
Hazard Class	9
ERG Code	9L

IMDG

UN/ID no	1950
Proper shipping name:	Aerosols, Limited Quantity (LQ)
Hazard Class	2
EmS-No	F-D, S-U

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
ZINC OXIDE - 1314-13-2	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations**California Proposition 65**

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PROPANE 74-98-6	X	X	X
HEPTANE 142-82-5	X	X	X
ZINC OXIDE 1314-13-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 18-Jul-2017

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet