



E8 Ester Refrigeration Lubricant 100 + U/V Dye

Safety Data Sheet

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products

Date of issue: 08/28/2014

Revision date: 08/28/2014

Supersedes: 06/17/2013

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : E8 Ester Refrigeration Lubricant 100 + U/V Dye
Product code : E8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Polyol Ester based lubricant with leak detection dye for use in air conditioning systems.

1.3. Details of the supplier of the safety data sheet

Tire Seal, Inc.
3574 Corona Street
33461 Lake Worth, Florida - USA
T 561-582-2245 - F 561-582-1499
www.supercool.ac

SDS Preparer Paul J. Erdek

1.4. Emergency telephone number

Emergency number : USA PHONE:1-800-373-7542, INT'L: 1-484-951-2432
DGA/AAG ENVIRONMENTAL CONTRACT: DGA4000-048

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

WHMIS Classification

Uncontrolled - Uncontrolled product according to WHMIS classification criteria

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
distillates (petroleum), hydrotreated light paraffinic	(CAS No) 64742-54-7	40 - 70	Not classified
HYDROGENATED POLYDECENE	(CAS No) 68037-01-4	5 - 18	Not classified
PENTAERYTHRITYL TETRA C5-10 ACID ESTERS	(CAS No) 68424-31-7	6 - 11	Not classified
diphenylamine	(CAS No) 122-39-4	0.1 - 0.7	Not classified
C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate, mixture of isomers	(CAS No) 125643-61-0	0.1 - 0.3	Not classified
phenyl isopropyl phosphate	(CAS No) 68937-41-7	0.1 - 0.3	Not classified
C.I. acid yellow 73	(CAS No) 518-47-8	0.1 - 0.11	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

E8 Ester Refrigeration Lubricant 100 + U/V Dye

Safety Data Sheet

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products

- | | |
|--------------------------------------|--|
| First-aid measures after eye contact | : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist. |
| First-aid measures after ingestion | : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

- | | |
|-------------------|--|
| Symptoms/injuries | : Not expected to present a significant hazard under anticipated conditions of normal use. |
|-------------------|--|

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- | | |
|--------------------------------|--|
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- | | |
|----------------------|-----------------------------------|
| Emergency procedures | : Evacuate unnecessary personnel. |
|----------------------|-----------------------------------|

6.1.2. For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |
|-------------------------|--|

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. |
|-------------------------------|--|

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|---|
| Storage conditions | : Store in original container. Keep cool. Keep container closed when not in use. Store in dry protected location to prevent any moisture contact. |
| Incompatible products | : Strong bases. Strong acids. |
| Incompatible materials | : Sources of ignition. Direct sunlight. |

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

- | | |
|-------------------------------|--|
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Hand protection | : The use of gloves impervious to the specific material handled is advised to prevent skin contact. Suggested protective material: Nitrile, 4.5 mil thickness, tested at 3.5 ml and above with no breakthrough time after 240 minutes. |
| Eye protection | : Chemical goggles or safety glasses. |
| Respiratory protection | : Normally not required. Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type R or P95 particle filters may be used. |

E8 Ester Refrigeration Lubricant 100 + U/V Dye

Safety Data Sheet

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colorless to light yellow.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 90 - 110 cSt @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: (Not expected to cause cancer. This oil meets the IP-346 criteria of less than 3 percent PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.)

E8 Ester Refrigeration Lubricant 100 + U/V Dye

Safety Data Sheet

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products

Reproductive toxicity	: Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met
Aspiration hazard	: Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects. Toxic to aquatic life.

12.2. Persistence and degradability

E8 Ester Refrigeration Lubricant 100 + U/V Dye

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

12.3. Bioaccumulative potential

E8 Ester Refrigeration Lubricant 100 + U/V Dye

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Disposal should be made in accordance with federal, state and local regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with TDG

TDG

No dangerous good in sense of transport regulations

No dangerous good in sense of transport regulations

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

CANADA

E8 Ester Refrigeration Lubricant 100 + U/V Dye

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

15.2. International regulations

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

E8 Ester Refrigeration Lubricant 100 + U/V Dye

Safety Data Sheet

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products


SECTION 16: Other information

Other information : None.

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



SDS Canada (GHS)

This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Tire Seal, Inc. The data on this sheet related only to the specific material designed herein. Tire Seal, Inc. assumes no legal responsibility for the use or reliance upon these data.