

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 07/28/2015

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.  
Product code : TM4277

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel Injector Cleaner

#### 1.3. Details of the supplier of the safety data sheet

REV YOUR CAUSE LLC  
1440 JASON WAY  
UNIT 100-107  
SANTA MARIA, CA 93455  
T 805-925-2796

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 4 H227  
Muta. 1B H340  
Carc. 1B H350  
Asp. Tox. 1 H304

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



GHS08

Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H227 - Combustible liquid  
H304 - May be fatal if swallowed and enters airways  
H340 - May cause genetic defects  
H350 - May cause cancer

Precautionary statements (GHS-US)

: P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P331 - Do NOT induce vomiting  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 3.2. Mixture

| Name                                        | Product identifier  | %            | Classification (GHS-US)                                                                                               |
|---------------------------------------------|---------------------|--------------|-----------------------------------------------------------------------------------------------------------------------|
| Distillates (Petroleum), Hydrotreated Light | (CAS No) 64742-47-8 | >= 95        | Asp. Tox. 1, H304                                                                                                     |
| Naphtha, Hydrotreated Heavy                 | (CAS No) 64742-48-9 | 0.13 - 1.215 | Muta. 1B, H340<br>Carc. 1B, H350<br>Asp. Tox. 1, H304                                                                 |
| Paraffins (Petroleum), Normal C5-20         | (CAS No) 64771-72-8 | < 1          | Not classified                                                                                                        |
| Xylene, Mixture of Isomers                  | (CAS No) 1330-20-7  | < 1          | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation:dust,mist), H332<br>Skin Irrit. 2, H315 |
| Ethylbenzene                                | (CAS No) 100-41-4   | < 1          | Flam. Liq. 2, H225<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Carc. 2, H351<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 |

The exact percentage is a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                                       |                                                                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). |
| First-aid measures after inhalation   | : Allow victim to breathe fresh air. Allow the victim to rest.                                                                    |
| First-aid measures after skin contact | : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.                 |
| First-aid measures after eye contact  | : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.                          |
| First-aid measures after ingestion    | : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.                                      |

### 4.2. Most important symptoms and effects, both acute and delayed

|                                      |                                                                                                                                     |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/injuries                    | : If you feel unwell, seek medical advice. May cause genetic defects. May cause cancer.                                             |
| Symptoms/injuries after inhalation   | : May cause allergy or asthma symptoms or breathing difficulties if inhaled.                                                        |
| Symptoms/injuries after skin contact | : May cause slight irritation . Itching. Red skin.                                                                                  |
| Symptoms/injuries after eye contact  | : May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. |
| Symptoms/injuries after ingestion    | : May be fatal if swallowed and enters airways.                                                                                     |

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Suitable extinguishing media   | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                     |

### 5.2. Special hazards arising from the substance or mixture

|                  |                                                   |
|------------------|---------------------------------------------------|
| Fire hazard      | : Combustible liquid.                             |
| Explosion hazard | : May form flammable/explosive vapor-air mixture. |

### 5.3. Advice for firefighters

|                                |                                                                                                                                                                   |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Firefighting instructions      | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection.                                                                   |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------|
| General measures | : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. |
|------------------|-----------------------------------------------------------------------------------------------------------|

#### 6.1.1. For non-emergency personnel

|                      |                                   |
|----------------------|-----------------------------------|
| Protective equipment | : Gloves. Safety glasses.         |
| Emergency procedures | : Evacuate unnecessary personnel. |

#### 6.1.2. For emergency responders

|                      |                                              |
|----------------------|----------------------------------------------|
| Protective equipment | : Equip cleanup crew with proper protection. |
|----------------------|----------------------------------------------|

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Remove contaminated clothes. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations. Ground/bond container and receiving equipment. Provide local exhaust or general room ventilation.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Ethylbenzene (100-41-4)                                  |                         |                 |
|----------------------------------------------------------|-------------------------|-----------------|
| USA ACGIH                                                | ACGIH TWA (ppm)         | 100 ppm         |
| USA ACGIH                                                | ACGIH STEL (ppm)        | 125 ppm         |
| USA OSHA                                                 | OSHA PEL (TWA) (mg/m³)  | 435 mg/m³       |
| USA OSHA                                                 | OSHA PEL (TWA) (ppm)    | 100             |
| USA OSHA                                                 | OSHA PEL (STEL) (mg/m³) | 545 mg/m³       |
| USA OSHA                                                 | OSHA PEL (STEL) (ppm)   | 125 ppm         |
| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |                         |                 |
| USA ACGIH                                                | ACGIH TWA (ppm)         | 200 ppm 8 Hours |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods. Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection : Wear respiratory protection.  
Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : Colourless to light yellow.  
Odor : Petroleum-like odour. Mild.  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 86 °C  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : 0.81  
Solubility : Insoluble in water.  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : 1.92 cSt @ 40 deg C  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : No data available

#### 9.2. Other information

VOC content : < 2 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| Ethylbenzene (100-41-4)    |                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------|
| LD50 oral rat              | 3500 mg/kg (Rat; Other; Experimental value)                                            |
| LD50 dermal rabbit         | 15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value) |
| LC50 inhalation rat (mg/l) | 17.8 mg/l/4h (Rat; Literature study)                                                   |

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                                                 |                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ethylbenzene (100-41-4)</b>                                  |                                                                                                                                                                                                                                         |
| LC50 inhalation rat (ppm)                                       | 4000 ppm/4h (Rat; Literature study)                                                                                                                                                                                                     |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                                                                                                                                                                                                                                         |
| LD50 oral rat                                                   | > 5000 mg/kg body weight                                                                                                                                                                                                                |
| LD50 dermal rabbit                                              | > 2000 mg/kg                                                                                                                                                                                                                            |
| LC50 inhalation rat (mg/l)                                      | > 5.28 mg/l/4h Based on lack of mortality and systemic effects                                                                                                                                                                          |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                   |                                                                                                                                                                                                                                         |
| LD50 oral rat                                                   | 3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value) |
| LD50 dermal rabbit                                              | > 4200.000000 mg/kg (Rabbit; Experimental value, Rabbit; Experimental value)                                                                                                                                                            |
| LC50 inhalation rat (mg/l)                                      | 29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)                                                                                                                                                            |
| <b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>         |                                                                                                                                                                                                                                         |
| LD50 oral rat                                                   | > 5000 mg/kg (Rat)                                                                                                                                                                                                                      |
| LD50 dermal rabbit                                              | > 2000 mg/kg (Rabbit)                                                                                                                                                                                                                   |
| Skin corrosion/irritation                                       | : Not classified                                                                                                                                                                                                                        |
| Serious eye damage/irritation                                   | : Not classified                                                                                                                                                                                                                        |
| Respiratory or skin sensitization                               | : Not classified                                                                                                                                                                                                                        |
| Germ cell mutagenicity                                          | : May cause genetic defects.                                                                                                                                                                                                            |
| Carcinogenicity                                                 | : May cause cancer.                                                                                                                                                                                                                     |

|                                                     |                                                                                                                                     |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ethylbenzene (100-41-4)</b>                      |                                                                                                                                     |
| IARC group                                          | 2B                                                                                                                                  |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>       |                                                                                                                                     |
| IARC group                                          | 3                                                                                                                                   |
| Reproductive toxicity                               | : Not classified                                                                                                                    |
| Specific target organ toxicity (single exposure)    | : Not classified                                                                                                                    |
| Specific target organ toxicity (repeated exposure)  | : Not classified                                                                                                                    |
| Aspiration hazard                                   | : May be fatal if swallowed and enters airways.                                                                                     |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met.                                                                 |
| Symptoms/injuries after inhalation                  | : May cause allergy or asthma symptoms or breathing difficulties if inhaled.                                                        |
| Symptoms/injuries after skin contact                | : May cause slight irritation . Itching. Red skin.                                                                                  |
| Symptoms/injuries after eye contact                 | : May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. |
| Symptoms/injuries after ingestion                   | : May be fatal if swallowed and enters airways.                                                                                     |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                |                                                                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Ethylbenzene (100-41-4)</b> |                                                                                                                                  |
| LC50 fish 2                    | 4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value) |

### 12.2. Persistence and degradability

|                                                                          |                                                                                                                                         |
|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.</b> |                                                                                                                                         |
| Persistence and degradability                                            | Not established.                                                                                                                        |
| <b>Ethylbenzene (100-41-4)</b>                                           |                                                                                                                                         |
| Persistence and degradability                                            | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.                                        |
| Biochemical oxygen demand (BOD)                                          | 1.44 g O <sub>2</sub> /g substance (20d.)                                                                                               |
| Chemical oxygen demand (COD)                                             | 2.1 g O <sub>2</sub> /g substance                                                                                                       |
| ThOD                                                                     | 3.17 g O <sub>2</sub> /g substance                                                                                                      |
| BOD (% of ThOD)                                                          | 45.4 (20 days)                                                                                                                          |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>          |                                                                                                                                         |
| Persistence and degradability                                            | Not established.                                                                                                                        |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                            |                                                                                                                                         |
| Persistence and degradability                                            | Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air. |

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                                                          |                                                                                                  |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>                  |                                                                                                  |
| Persistence and degradability                                            | Readily biodegradable in water.                                                                  |
| <b>Distillates, Hydrotreated Light (64742-47-8)</b>                      |                                                                                                  |
| Persistence and degradability                                            | Not established.                                                                                 |
| <b>Naphtha, Hydrotreated Heavy (64742-48-9)</b>                          |                                                                                                  |
| Persistence and degradability                                            | Not established.                                                                                 |
| <b>12.3. Bioaccumulative potential</b>                                   |                                                                                                  |
| <b>THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.</b> |                                                                                                  |
| Bioaccumulative potential                                                | Not established.                                                                                 |
| <b>Ethylbenzene (100-41-4)</b>                                           |                                                                                                  |
| BCF fish 1                                                               | 1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study) |
| BCF fish 2                                                               | 15 - 79 (BCF)                                                                                    |
| BCF other aquatic organisms 1                                            | 4.68 (BCF)                                                                                       |
| Log Pow                                                                  | 3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)  |
| Bioaccumulative potential                                                | Low potential for bioaccumulation (BCF < 500).                                                   |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>          |                                                                                                  |
| Bioaccumulative potential                                                | Not established.                                                                                 |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                            |                                                                                                  |
| BCF fish 2                                                               | 7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)                     |
| Log Pow                                                                  | 3.2 (Conclusion by analogy; 20 °C)                                                               |
| Bioaccumulative potential                                                | Low potential for bioaccumulation (BCF < 500).                                                   |
| <b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>                  |                                                                                                  |
| Bioaccumulative potential                                                | No bioaccumulation data available.                                                               |
| <b>Distillates, Hydrotreated Light (64742-47-8)</b>                      |                                                                                                  |
| Bioaccumulative potential                                                | Not established.                                                                                 |
| <b>Naphtha, Hydrotreated Heavy (64742-48-9)</b>                          |                                                                                                  |
| Bioaccumulative potential                                                | Not established.                                                                                 |
| <b>12.4. Mobility in soil</b>                                            |                                                                                                  |
| <b>Ethylbenzene (100-41-4)</b>                                           |                                                                                                  |
| Surface tension                                                          | 0.029 N/m                                                                                        |
| Log Koc                                                                  | log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value     |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                            |                                                                                                  |
| Ecology - soil                                                           | May be harmful to plant growth, blooming and fruit formation.                                    |

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): NA1993, Combustible liquid, n.o.s.(Petroleum Distillates), 3, III, Limited Quantity  
ICAO/IATA (air): Not regulated,  
IMO/IMDG (water): Not regulated,  
Special Provisions: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.(Petroleum Distillates)  
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name  
Packing group (DOT) : III - Minor Danger  
DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 241

#### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

|                                     |                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |
|-------------------------------------|-----------------------------------------------------------------------------------|

##### Ethylbenzene (100-41-4)

|                                                                                                                                                  |                                                                                   |
|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Subject to reporting requirements of United States SARA Section 313<br>Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                   |
| SARA Section 311/312 Hazard Classes                                                                                                              | Immediate (acute) health hazard<br>Fire hazard<br>Delayed (chronic) health hazard |

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                     |                                                                    |
|-------------------------------------|--------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|--------------------------------------------------------------------|

### Xylene, Mixture of Isomers (1330-20-7)

|                                     |             |
|-------------------------------------|-------------|
| SARA Section 311/312 Hazard Classes | Fire hazard |
|-------------------------------------|-------------|

## 15.2. International regulations

### CANADA

#### THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

|                      |                                         |
|----------------------|-----------------------------------------|
| WHMIS Classification | Class B Division 3 - Combustible Liquid |
|----------------------|-----------------------------------------|

#### Ethylbenzene (100-41-4)

|                                                       |
|-------------------------------------------------------|
| Listed on the Canadian DSL (Domestic Substances List) |
|-------------------------------------------------------|

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                                       |
|-------------------------------------------------------|
| Listed on the Canadian DSL (Domestic Substances List) |
|-------------------------------------------------------|

|                      |                                                                 |
|----------------------|-----------------------------------------------------------------|
| WHMIS Classification | Uncontrolled product according to WHMIS classification criteria |
|----------------------|-----------------------------------------------------------------|

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Muta.Cat.2; R46

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### Ethylbenzene (100-41-4)

|                                                                                           |
|-------------------------------------------------------------------------------------------|
| Listed on the AICS (Australian Inventory of Chemical Substances)                          |
| Listed on NZIoC (New Zealand Inventory of Chemicals)                                      |
| Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory                |
| Listed on KECI (Korean Existing Chemicals Inventory)                                      |
| Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)              |
| Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) |

## 15.3. US State regulations

### THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

|                                                                     |                                                                           |
|---------------------------------------------------------------------|---------------------------------------------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List               | No                                                                        |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No                                                                        |
| State or local regulations                                          | U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) |

#### Ethylbenzene (100-41-4)

|                                                       |                                                             |                                                                     |                                                                   |                                  |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| Yes                                                   | No                                                          | No                                                                  | No                                                                |                                  |

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                                       |                                                             |                                                                     |                                                                   |                                  |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                  |

# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Xylene, Mixture of Isomers (1330-20-7)                                                                                                                                                    |                                                             |                                                                     |                                                                   |                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List                                                                                                                                     | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No                                                                                                                                                                                        | No                                                          | No                                                                  | No                                                                |                                  |
| Paraffins (Petroleum), Normal C5-20 (64771-72-8)                                                                                                                                          |                                                             |                                                                     |                                                                   |                                  |
| U.S. - California - Proposition 65 - Carcinogens List                                                                                                                                     | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No                                                                                                                                                                                        | No                                                          | No                                                                  | No                                                                |                                  |
| Distillates, Hydrotreated Light (64742-47-8)                                                                                                                                              |                                                             |                                                                     |                                                                   |                                  |
| U.S. - California - Proposition 65 - Carcinogens List                                                                                                                                     | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No                                                                                                                                                                                        | No                                                          | No                                                                  | No                                                                |                                  |
| Naphtha, Hydrotreated Heavy (64742-48-9)                                                                                                                                                  |                                                             |                                                                     |                                                                   |                                  |
| U.S. - California - Proposition 65 - Carcinogens List                                                                                                                                     | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No                                                                                                                                                                                        | No                                                          | No                                                                  | No                                                                |                                  |
| Ethylbenzene (100-41-4)                                                                                                                                                                   |                                                             |                                                                     |                                                                   |                                  |
| State or local regulations                                                                                                                                                                |                                                             |                                                                     |                                                                   |                                  |
| U.S. - Pennsylvania - RTK (Right to Know) List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) |                                                             |                                                                     |                                                                   |                                  |

## SECTION 16: Other information


Other information : None.

Full text of H-phrases:

|                                     |                                                                   |
|-------------------------------------|-------------------------------------------------------------------|
| Acute Tox. 4 (Dermal)               | Acute toxicity (dermal) Category 4                                |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4                  |
| Acute Tox. 4 (Inhalation:vapour)    | Acute toxicity (inhalation:vapour) Category 4                     |
| Asp. Tox. 1                         | Aspiration hazard Category 1                                      |
| Carc. 1B                            | Carcinogenicity Category 1B                                       |
| Carc. 2                             | Carcinogenicity Category 2                                        |
| Flam. Liq. 2                        | Flammable liquids Category 2                                      |
| Flam. Liq. 3                        | Flammable liquids Category 3                                      |
| Flam. Liq. 4                        | Flammable liquids Category 4                                      |
| Muta. 1B                            | Germ cell mutagenicity Category 1B                                |
| Skin Irrit. 2                       | Skin corrosion/irritation Category 2                              |
| STOT RE 2                           | Specific target organ toxicity (repeated exposure) Category 2     |
| H225                                | Highly flammable liquid and vapor                                 |
| H226                                | Flammable liquid and vapor                                        |
| H227                                | Combustible liquid                                                |
| H304                                | May be fatal if swallowed and enters airways                      |
| H312                                | Harmful in contact with skin                                      |
| H315                                | Causes skin irritation                                            |
| H332                                | Harmful if inhaled                                                |
| H340                                | May cause genetic defects                                         |
| H350                                | May cause cancer                                                  |
| H351                                | Suspected of causing cancer                                       |
| H373                                | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.



# THROTTLE MUSCLE THROTTLE POWER PRO FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

|                  |                                                                                                      |
|------------------|------------------------------------------------------------------------------------------------------|
| NFPA fire hazard | : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur. |
| NFPA reactivity  | : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.         |

### HMIS III Rating

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| Health              | : 2 Moderate Hazard - Temporary or minor injury may occur |
| Flammability        | : 2 Moderate Hazard                                       |
| Physical            | : 0 Minimal Hazard                                        |
| Personal Protection | : B                                                       |

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/28/2014

Version:

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.  
Product code : TM6239

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel Injector Cleaner

#### 1.3. Details of the supplier of the safety data sheet

REV YOUR CAUSE LLC  
1440 JASON WAY  
UNIT 100-107  
SANTA MARIA, CA 93455  
T 805-925-2796

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Carc. 2 H351  
Repr. 2 H361

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

GHS07

GHS08

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H351 - Suspected of causing cancer  
H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS-US) : P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, ventilating, lighting equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P264 - Wash affected areas thoroughly after handling  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P321 - Specific treatment: See section 4.1 on SDS  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                                        | Product identifier  | %            | Classification (GHS-US)                                                                                               |
|---------------------------------------------|---------------------|--------------|-----------------------------------------------------------------------------------------------------------------------|
| Xylene, Mixture of Isomers                  | (CAS No) 1330-20-7  | 46.4 - 58    | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315                                                                             |
| 1-Methoxy-2-Propanol                        | (CAS No) 107-98-2   | 19.9 - 20    | Flam. Liq. 3, H226                                                                                                    |
| Distillates (Petroleum), Hydrotreated Light | (CAS No) 64742-47-8 | 10 - 30      | Asp. Tox. 1, H304                                                                                                     |
| Ethylbenzene                                | (CAS No) 100-41-4   | 8.7 - 11.6   | Flam. Liq. 2, H225<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Carc. 2, H351                                         |
| Stoddard Solvent                            | (CAS No) 8052-41-3  | < 1          | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312                                        |
| Toluene                                     | (CAS No) 108-88-3   | 0.058 - 0.29 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 |
| 2-Methoxypropanol                           | (CAS No) 1589-47-5  | 0 - 0.1      | Flam. Liq. 3, H226                                                                                                    |

The exact percentage is a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child.

Symptoms/injuries after inhalation : May cause irritation or asthma-like symptoms.

Symptoms/injuries after skin contact : Causes skin irritation. Itching. Red skin. Skin rash/inflammation.

Symptoms/injuries after eye contact : May cause slight eye irritation. Redness of the eye tissue. Irritation of the eye tissue. Inflammation/damage of the eye tissue.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions. Do not handle until all safety precautions have been read and understood.  
Hygiene measures : Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Stoddard Solvent (8052-41-3)           |                        |            |
|----------------------------------------|------------------------|------------|
| USA ACGIH                              | ACGIH TWA (ppm)        | 100 ppm    |
| USA OSHA                               | OSHA PEL (TWA) (mg/m³) | 2900 mg/m³ |
| USA OSHA                               | OSHA PEL (TWA) (ppm)   | 500 ppm    |
| Xylene, Mixture of Isomers (1330-20-7) |                        |            |
| USA ACGIH                              | ACGIH TWA (ppm)        | 100 ppm    |
| USA ACGIH                              | ACGIH STEL (ppm)       | 100 ppm    |
| Ethylbenzene (100-41-4)                |                        |            |
| USA ACGIH                              | ACGIH TWA (ppm)        | 100 ppm    |
| USA ACGIH                              | ACGIH STEL (ppm)       | 125 ppm    |
| USA OSHA                               | OSHA PEL (TWA) (mg/m³) | 435 mg/m³  |
| USA OSHA                               | OSHA PEL (TWA) (ppm)   | 100        |

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Ethylbenzene (100-41-4)                                  |                          |                 |
|----------------------------------------------------------|--------------------------|-----------------|
| USA OSHA                                                 | OSHA PEL (STEL) (mg/m³)  | 545 mg/m³       |
| USA OSHA                                                 | OSHA PEL (STEL) (ppm)    | 125 ppm         |
| Toluene (108-88-3)                                       |                          |                 |
| USA ACGIH                                                | ACGIH TWA (mg/m³)        | 75 mg/m³        |
| USA ACGIH                                                | ACGIH TWA (ppm)          | 20 ppm          |
| USA OSHA                                                 | OSHA PEL (TWA) (ppm)     | 200 ppm         |
| USA OSHA                                                 | OSHA PEL (Ceiling) (ppm) | 300 ppm         |
| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |                          |                 |
| USA ACGIH                                                | ACGIH TWA (ppm)          | 200 ppm 8 Hours |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods.  
Personal protective equipment : Safety glasses. Gloves. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Wear appropriate mask.  
Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : Colourless to light yellow.  
Odor : Characteristic.  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : 57.8 °C (Lowest Component)  
Flash point : 32 °C  
Auto-ignition temperature : 464 °C (Lowest Component)  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : 0.87  
Solubility : Insoluble in water.  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : No data available

### 9.2. Other information

VOC content : 78 %

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| 1-Methoxy-2-Propanol (107-98-2)                          |                                                                                                                                                                                                                                         |
|----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat                                            | 6600 mg/kg (Rat; Other; Literature study; 4016 mg/kg bodyweight; Rat; Experimental value)                                                                                                                                               |
| LD50 dermal rat                                          | > 2000 mg/kg body weight (Rat; Experimental value; Other)                                                                                                                                                                               |
| LD50 dermal rabbit                                       | 13000 mg/kg (Rabbit; Literature study)                                                                                                                                                                                                  |
| LC50 inhalation rat (mg/l)                               | 55 mg/l/4h (Rat; Literature study)                                                                                                                                                                                                      |
| LC50 inhalation rat (ppm)                                | 15000 ppm/4h (Rat; Literature study)                                                                                                                                                                                                    |
| 2-Methoxypropanol (1589-47-5)                            |                                                                                                                                                                                                                                         |
| LD50 oral rat                                            | 5710 mg/kg (Rat)                                                                                                                                                                                                                        |
| Xylene, Mixture of Isomers (1330-20-7)                   |                                                                                                                                                                                                                                         |
| LD50 oral rat                                            | 3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value) |
| LD50 dermal rabbit                                       | > 4200.000000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)                                                                                                                                                             |
| LC50 inhalation rat (mg/l)                               | 29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)                                                                                                                                                            |
| Ethylbenzene (100-41-4)                                  |                                                                                                                                                                                                                                         |
| LD50 oral rat                                            | 3500 mg/kg (Rat; Other; Experimental value)                                                                                                                                                                                             |
| LD50 dermal rabbit                                       | 15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)                                                                                                                                                  |
| LC50 inhalation rat (mg/l)                               | 17.8 mg/l/4h (Rat; Literature study)                                                                                                                                                                                                    |
| LC50 inhalation rat (ppm)                                | 4000 ppm/4h (Rat; Literature study)                                                                                                                                                                                                     |
| Toluene (108-88-3)                                       |                                                                                                                                                                                                                                         |
| LD50 oral rat                                            | 5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)                                                                                                       |
| LD50 dermal rabbit                                       | > 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)                                                                                                                                                  |
| LC50 inhalation rat (mg/l)                               | > 28.1 mg/l/4h (Rat; Air, Literature study)                                                                                                                                                                                             |
| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |                                                                                                                                                                                                                                         |
| LD50 oral rat                                            | > 5000 mg/kg body weight                                                                                                                                                                                                                |
| LD50 dermal rabbit                                       | > 2000 mg/kg                                                                                                                                                                                                                            |
| LC50 inhalation rat (mg/l)                               | > 5.28 mg/l/4h Based on lack of mortality and systemic effects                                                                                                                                                                          |
| Skin corrosion/irritation                                | : Causes skin irritation.                                                                                                                                                                                                               |
| Serious eye damage/irritation                            | : Not classified                                                                                                                                                                                                                        |
| Respiratory or skin sensitization                        | : Not classified                                                                                                                                                                                                                        |
| Germ cell mutagenicity                                   | : Not classified                                                                                                                                                                                                                        |
| Carcinogenicity                                          | : Suspected of causing cancer.                                                                                                                                                                                                          |
| Xylene, Mixture of Isomers (1330-20-7)                   |                                                                                                                                                                                                                                         |
| IARC group                                               | 3                                                                                                                                                                                                                                       |
| Ethylbenzene (100-41-4)                                  |                                                                                                                                                                                                                                         |
| IARC group                                               | 2B                                                                                                                                                                                                                                      |

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Toluene (108-88-3)</b>                           |                                                                                                                                     |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| IARC group                                          | 3                                                                                                                                   |
| Reproductive toxicity                               | : Suspected of damaging fertility or the unborn child.                                                                              |
| Specific target organ toxicity (single exposure)    | : Not classified                                                                                                                    |
| Specific target organ toxicity (repeated exposure)  | : Not classified                                                                                                                    |
| Aspiration hazard                                   | : Not classified                                                                                                                    |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met.                                                                 |
| Symptoms/injuries after inhalation                  | : May cause irritation or asthma-like symptoms.                                                                                     |
| Symptoms/injuries after skin contact                | : Causes skin irritation. Itching. Red skin. Skin rash/inflammation.                                                                |
| Symptoms/injuries after eye contact                 | : May cause slight eye irritation . Redness of the eye tissue. Irritation of the eye tissue. Inflammation/damage of the eye tissue. |
| Symptoms/injuries after ingestion                   | : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.                                     |

## SECTION 12: Ecological information

### 12.1. Toxicity

| <b>1-Methoxy-2-Propanol (107-98-2)</b>        |                                                                   |
|-----------------------------------------------|-------------------------------------------------------------------|
| LC50 fish 1                                   | 4600 - 10000 mg/l (96 h; Leuciscus idus; Nominal concentration)   |
| EC50 Daphnia 1                                | 23300 mg/l (48 h; Daphnia magna; Nominal concentration)           |
| LC50 fish 2                                   | 20800 mg/l (96 h; Pimephales promelas)                            |
| Threshold limit algae 1                       | > 1000 mg/l (168 h; Pseudokirchneriella subcapitata; Growth rate) |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b> |                                                                   |
| LC50 fish 1                                   | 13.5 mg/l (96 h; Lepomis macrochirus; Lethal)                     |
| EC50 Daphnia 1                                | 150 mg/l (24 h; Daphnia magna)                                    |
| LC50 fish 2                                   | 3.77 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)             |
| EC50 Daphnia 2                                | 7.4 mg/l (48 h; Daphnia magna)                                    |
| Threshold limit algae 1                       | 72 mg/l (336 h; Selenastrum capricornutum; Growth)                |
| Threshold limit algae 2                       | 10 mg/l (72 h; Skeletonema costatum)                              |
| <b>Ethylbenzene (100-41-4)</b>                |                                                                   |
| LC50 fish 1                                   | 9.09 mg/l (96 h; Pimephales promelas)                             |
| EC50 Daphnia 1                                | 77 mg/l (24 h; Daphnia magna)                                     |
| EC50 other aquatic organisms 1                | 48 mg/l (72 h; Scenedesmus subspicatus)                           |
| LC50 fish 2                                   | 4.2 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)              |
| EC50 Daphnia 2                                | 75 mg/l (48 h; Daphnia magna)                                     |
| TLM fish 1                                    | 29 ppm (96 h; Lepomis macrochirus; Hard water)                    |
| TLM fish 2                                    | 42.3 mg/l (96 h; Pimephales promelas)                             |
| TLM other aquatic organisms 1                 | 10 - 100,96 h                                                     |
| Threshold limit algae 1                       | > 160 mg/l (192 h; Scenedesmus quadricauda; Toxicity test)        |
| Threshold limit algae 2                       | 33 mg/l (192 h; Microcystis aeruginosa; Toxicity test)            |
| <b>Toluene (108-88-3)</b>                     |                                                                   |
| LC50 fish 1                                   | 24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)               |
| EC50 Daphnia 1                                | 84 mg/l (24 h; Daphnia magna; Locomotor effect)                   |
| LC50 fish 2                                   | 13 mg/l (96 h; Lepomis macrochirus)                               |
| EC50 Daphnia 2                                | 11.5 - 19.6 mg/l (48 h; Daphnia magna)                            |
| Threshold limit algae 1                       | > 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)        |
| Threshold limit algae 2                       | 105 mg/l (192 h; Microcystis aeruginosa)                          |

### 12.2. Persistence and degradability

| <b>THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.</b> |                                                                                                                  |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Persistence and degradability                      | Not established.                                                                                                 |
| <b>Stoddard Solvent (8052-41-3)</b>                |                                                                                                                  |
| Persistence and degradability                      | Not established.                                                                                                 |
| <b>1-Methoxy-2-Propanol (107-98-2)</b>             |                                                                                                                  |
| Persistence and degradability                      | Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. |
| ThOD                                               | 1.95 g O <sub>2</sub> /g substance                                                                               |
| <b>2-Methoxypropanol (1589-47-5)</b>               |                                                                                                                  |
| Persistence and degradability                      | Biodegradability in water: no data available.                                                                    |

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                                                 |                                                                                                                                         |
|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                   |                                                                                                                                         |
| Persistence and degradability                                   | Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air. |
| <b>Ethylbenzene (100-41-4)</b>                                  |                                                                                                                                         |
| Persistence and degradability                                   | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.                                        |
| Biochemical oxygen demand (BOD)                                 | 1.44 g O <sub>2</sub> /g substance (20d.)                                                                                               |
| Chemical oxygen demand (COD)                                    | 2.1 g O <sub>2</sub> /g substance                                                                                                       |
| ThOD                                                            | 3.17 g O <sub>2</sub> /g substance                                                                                                      |
| BOD (% of ThOD)                                                 | (20 day(s)) 45.4                                                                                                                        |
| <b>Toluene (108-88-3)</b>                                       |                                                                                                                                         |
| Persistence and degradability                                   | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.                                        |
| Biochemical oxygen demand (BOD)                                 | 2.15 g O <sub>2</sub> /g substance                                                                                                      |
| Chemical oxygen demand (COD)                                    | 2.52 g O <sub>2</sub> /g substance                                                                                                      |
| ThOD                                                            | 3.13 g O <sub>2</sub> /g substance                                                                                                      |
| BOD (% of ThOD)                                                 | 0.69 % ThOD                                                                                                                             |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                                                                                                                                         |
| Persistence and degradability                                   | Not established.                                                                                                                        |
| <b>12.3. Bioaccumulative potential</b>                          |                                                                                                                                         |
| <b>THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.</b>              |                                                                                                                                         |
| Bioaccumulative potential                                       | Not established.                                                                                                                        |
| <b>Stoddard Solvent (8052-41-3)</b>                             |                                                                                                                                         |
| Log Pow                                                         | 3.16-7.06                                                                                                                               |
| Bioaccumulative potential                                       | Not established.                                                                                                                        |
| <b>1-Methoxy-2-Propanol (107-98-2)</b>                          |                                                                                                                                         |
| BCF fish 1                                                      | 1 (Pimephales promelas)                                                                                                                 |
| Bioaccumulative potential                                       | Low potential for bioaccumulation (Log Kow < 4).                                                                                        |
| <b>2-Methoxypropanol (1589-47-5)</b>                            |                                                                                                                                         |
| Log Pow                                                         | -0.49 (Estimated value)                                                                                                                 |
| Bioaccumulative potential                                       | Bioaccumulation: not applicable.                                                                                                        |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                   |                                                                                                                                         |
| BCF fish 1                                                      | 15 8 weeks; Salmo gairdneri (Oncorhynchus mykiss)                                                                                       |
| BCF fish 2                                                      | 7 - 26 (8 weeks; Oncorhynchus mykiss)                                                                                                   |
| Log Pow                                                         | 3.2 (Conclusion by analogy; 20 °C)                                                                                                      |
| Bioaccumulative potential                                       | Low potential for bioaccumulation (BCF < 500).                                                                                          |
| <b>Ethylbenzene (100-41-4)</b>                                  |                                                                                                                                         |
| BCF fish 1                                                      | 1 (6 weeks; Oncorhynchus kisutch)                                                                                                       |
| BCF fish 2                                                      | 15 - 79 (Carassius auratus)                                                                                                             |
| BCF other aquatic organisms 1                                   | 4.68 (Lamellibranchiata)                                                                                                                |
| Log Pow                                                         | 3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)                                         |
| Bioaccumulative potential                                       | Low potential for bioaccumulation (BCF < 500).                                                                                          |
| <b>Toluene (108-88-3)</b>                                       |                                                                                                                                         |
| BCF fish 1                                                      | 13.2 (Anguilla japonica)                                                                                                                |
| BCF fish 2                                                      | 90 (72 h; Leuciscus idus)                                                                                                               |
| BCF other aquatic organisms 1                                   | 380 (24 h; Chlorella sp.; Fresh weight)                                                                                                 |
| BCF other aquatic organisms 2                                   | 4.2 (Mytilus edulis; Fresh weight)                                                                                                      |
| Log Pow                                                         | 2.73 (Experimental value; Other; 20 °C)                                                                                                 |
| Bioaccumulative potential                                       | Low potential for bioaccumulation (BCF < 500).                                                                                          |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                                                                                                                                         |
| Bioaccumulative potential                                       | Not established.                                                                                                                        |
| <b>12.4. Mobility in soil</b>                                   |                                                                                                                                         |
| <b>Xylene, Mixture of Isomers (1330-20-7)</b>                   |                                                                                                                                         |
| Ecology - soil                                                  | May be harmful to plant growth, blooming and fruit formation.                                                                           |
| <b>Ethylbenzene (100-41-4)</b>                                  |                                                                                                                                         |
| Surface tension                                                 | 0.029 N/m                                                                                                                               |
| <b>Toluene (108-88-3)</b>                                       |                                                                                                                                         |
| Surface tension                                                 | 0.03 N/m (20 °C)                                                                                                                        |

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1993, Flammable liquids, n.o.s (Xylene, Petroleum Distillates), 3, III, Limited Quantity

ICAO/IATA (air): UN1993, Flammable liquids, n.o.s (Xylene, Petroleum Distillates), 3, III, Limited Quantity

IMO/IMDG (water): UN1993, Flammable liquids, n.o.s (Xylene, Petroleum Distillates), 3, III, Limited Quantity

Special Provisions: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s (Xylene, Petroleum Distillates)

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

|                                     |                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |
|-------------------------------------|-----------------------------------------------------------------------------------|

#### Stoddard Solvent (8052-41-3)

|                                     |                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |
|-------------------------------------|-----------------------------------------------------------------------------------|

#### Xylene, Mixture of Isomers (1330-20-7)

|                                     |             |
|-------------------------------------|-------------|
| SARA Section 311/312 Hazard Classes | Fire hazard |
|-------------------------------------|-------------|

#### Ethylbenzene (100-41-4)

|                                                                                                                       |                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Listed on United States SARA Section 313<br>Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                   |
| SARA Section 311/312 Hazard Classes                                                                                   | Immediate (acute) health hazard<br>Fire hazard<br>Delayed (chronic) health hazard |

#### Toluene (108-88-3)

|                                                                                                                                                                       |                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Listed on United States SARA Section 313<br>Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on the United States SARA Section 302 |                                                                                   |
| SARA Section 311/312 Hazard Classes                                                                                                                                   | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                     |                                                                    |
|-------------------------------------|--------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|--------------------------------------------------------------------|

### 15.2. International regulations

#### CANADA

#### THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

|                      |                                       |
|----------------------|---------------------------------------|
| WHMIS Classification | Class B Division 2 - Flammable Liquid |
|----------------------|---------------------------------------|

#### Stoddard Solvent (8052-41-3)

|                      |                                                                                                                          |
|----------------------|--------------------------------------------------------------------------------------------------------------------------|
| WHMIS Classification | Class B Division 3 - Combustible Liquid<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|----------------------|--------------------------------------------------------------------------------------------------------------------------|

#### Ethylbenzene (100-41-4)

|                                                       |  |
|-------------------------------------------------------|--|
| Listed on the Canadian DSL (Domestic Substances List) |  |
|-------------------------------------------------------|--|

#### Toluene (108-88-3)

|                                                       |                                                                                                                                                                                                              |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Listed on the Canadian DSL (Domestic Substances List) |                                                                                                                                                                                                              |
| WHMIS Classification                                  | Class B Division 2 - Flammable Liquid<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                      |                                                                 |
|----------------------|-----------------------------------------------------------------|
| WHMIS Classification | Uncontrolled product according to WHMIS classification criteria |
|----------------------|-----------------------------------------------------------------|

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### EU-Regulations

#### Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Muta.Cat.2; R46

Xn; R20/21

Xi; R38

R10

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### Ethylbenzene (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

#### Toluene (108-88-3)

### 15.3. US State regulations

#### THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

|                                                                     |                                                                           |
|---------------------------------------------------------------------|---------------------------------------------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List               | No                                                                        |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No                                                                        |
| State or local regulations                                          | U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) |

#### Stoddard Solvent (8052-41-3)

|                                                       |                                                             |                                                                     |                                                                   |                                   |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                   |

#### 1-Methoxy-2-Propanol (107-98-2)

|                                                       |                                                             |                                                                     |                                                                   |                                   |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                   |

#### 2-Methoxypropanol (1589-47-5)

|                                                       |                                                             |                                                                     |                                                                   |                                   |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                   |

#### Xylene, Mixture of Isomers (1330-20-7)

|                                                       |                                                             |                                                                     |                                                                   |                                   |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                   |

#### Ethylbenzene (100-41-4)

|                                                       |                                                             |                                                                     |                                                                   |                                   |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                   |

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Ethylbenzene (100-41-4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                             |                                                                     |                                                                   |                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                             | Female                                                              | Male                                                              |                                   |
| Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | No                                                          | No                                                                  | No                                                                |                                   |
| Toluene (108-88-3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                                                                                                                                                                                                                                                                                                                                                                                                                                     | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Yes                                                         | No                                                                  | No                                                                |                                   |
| Distillates (Petroleum), Hydrotreated Light (64742-47-8)                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                                                                                                                                                                                                                                                                                                                                                                                                                                     | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | No                                                          | No                                                                  | No                                                                |                                   |
| Ethylbenzene (100-41-4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                             |                                                                     |                                                                   |                                   |
| State or local regulations                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                             |                                                                     |                                                                   |                                   |
| U.S. - Pennsylvania - RTK (Right to Know) List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)                                                                                                                                                                                                                                                                                                 |                                                             |                                                                     |                                                                   |                                   |
| Toluene (108-88-3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                             |                                                                     |                                                                   |                                   |
| State or local regulations                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)<br>U.S. - New Jersey - Special Health Hazards Substances List<br>New Jersey Right-to-Know<br>U.S. - Massachusetts - Right To Know List<br>Rhode Island Right to Know<br>U.S. - Michigan - Critical Materials List<br>U.S. - New Jersey - Environmental Hazardous Substances List<br>U.S. - Illinois - Toxic Air Contaminants<br>U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances |                                                             |                                                                     |                                                                   |                                   |

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:


|                                  |                                                                   |
|----------------------------------|-------------------------------------------------------------------|
| Acute Tox. 4 (Dermal)            | Acute toxicity (dermal) Category 4                                |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4                     |
| Acute Tox. 4 (Oral)              | Acute toxicity (oral) Category 4                                  |
| Asp. Tox. 1                      | Aspiration hazard Category 1                                      |
| Carc. 2                          | Carcinogenicity Category 2                                        |
| Flam. Liq. 2                     | Flammable liquids Category 2                                      |
| Flam. Liq. 3                     | Flammable liquids Category 3                                      |
| Repr. 2                          | Reproductive toxicity Category 2                                  |
| Skin Irrit. 2                    | Skin corrosion/irritation Category 2                              |
| STOT RE 2                        | Specific target organ toxicity (repeated exposure) Category 2     |
| STOT SE 3                        | Specific target organ toxicity (single exposure) Category 3       |
| H225                             | Highly flammable liquid and vapor                                 |
| H226                             | Flammable liquid and vapor                                        |
| H302                             | Harmful if swallowed                                              |
| H304                             | May be fatal if swallowed and enters airways                      |
| H312                             | Harmful in contact with skin                                      |
| H315                             | Causes skin irritation                                            |
| H332                             | Harmful if inhaled                                                |
| H336                             | May cause drowsiness or dizziness                                 |
| H351                             | Suspected of causing cancer                                       |
| H361                             | Suspected of damaging fertility or the unborn child               |
| H373                             | May cause damage to organs through prolonged or repeated exposure |

# THROTTLE MUSCLE INDUCTION CLEANER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                    |                                                                                                                                                |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| NFPA health hazard | : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given. |
| NFPA fire hazard   | : 3 - Liquids and solids that can be ignited under almost all ambient conditions.                                                              |
| NFPA reactivity    | : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.                                                   |



### HMIS III Rating

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| Health              | : 2 Moderate Hazard - Temporary or minor injury may occur |
| Flammability        | : 3 Serious Hazard                                        |
| Physical            | : 0 Minimal Hazard                                        |
| Personal Protection | : B                                                       |

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*