

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/26/2015

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.
Product code : TM8674
Other means of identification : This diesel fuel additive complies with federal low sulfur content requirements for use in diesel motor vehicles and nonroad engines.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Diesel Fuel Additive

1.3. Details of the supplier of the safety data sheet

Rev Your Cause LLC
1440 Jason Way
Unit 100-107
Santa Maria, CA 93455
T 805-925-2796

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226
Muta. 1B H340
Carc. 2 H351
Asp. Tox. 1 H304

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

GHS08

Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H340 - May cause genetic defects
H351 - Suspected of causing cancer

Precautionary statements (GHS-US)

: P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, ventilating, lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P308+P313 - If exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Light	(CAS No) 64742-47-8	70 - 85	Asp. Tox. 1, H304
Solvent Naphtha (Petroleum), Light Aromatic	(CAS No) 64742-95-6	10 - 30	Flam. Liq. 2, H225 Muta. 1B, H340 Asp. Tox. 1, H304
2-Ethylhexyl Nitrate	(CAS No) 27247-96-7	5 - 10	Not classified
Butyl Glycoether	(CAS No) 111-76-2	1.39 - 5.56	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
1,2,4-Trimethylbenzene	(CAS No) 95-63-6	< 0.556	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
Xylene, Mixture of Isomers	(CAS No) 1330-20-7	< 0.556	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
Trimethylbenzenes	(CAS No) 25551-13-7	< 0.556	Flam. Liq. 3, H226
Ethylbenzene	(CAS No) 100-41-4	< 0.139	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
Vinyl Acetate	(CAS No) 108-05-4	< 0.0278	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT SE 3, H335

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause genetic defects.

Symptoms/injuries after inhalation : May cause irritation or asthma-like symptoms. May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause slight irritation . May cause an allergic skin reaction.

Symptoms/injuries after eye contact : May cause slight eye irritation . May cause slight irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Always wash hands after handling the product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butyl Glycoether (111-76-2)

USA ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
-----------	-----------------	---

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethylbenzene (95-63-6)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Ethylbenzene (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	125 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100
USA OSHA	OSHA PEL (STEL) (mg/m³)	545 mg/m³
USA OSHA	OSHA PEL (STEL) (ppm)	125 ppm
Vinyl Acetate (108-05-4)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm (Vinyl acetate; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	15 ppm (Vinyl acetate; USA; Short time value; TLV - Adopted Value)

8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
 Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.
 Eye protection : Chemical goggles or safety glasses.
 Skin and body protection : Wear suitable protective clothing.
 Respiratory protection : Wear respiratory protection.
 Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
 Appearance : Liquid.
 Color : Amber.
 Odor : Hydrocarbon.
 Odor threshold : No data available
 pH : No data available
 Relative evaporation rate (butyl acetate=1) : No data available
 Melting point : No data available
 Freezing point : No data available
 Boiling point : No data available
 Flash point : 48.9 °C Lowest Component
 Auto-ignition temperature : No data available
 Decomposition temperature : No data available
 Flammability (solid, gas) : No data available
 Vapor pressure : No data available
 Relative vapor density at 20 °C : No data available
 Relative density : 0.822 @ 20 deg C
 Solubility : Insoluble in water.
 Log Pow : No data available
 Log Kow : No data available
 Viscosity, kinematic : No data available
 Viscosity, dynamic : No data available
 Explosive properties : No data available
 Oxidizing properties : No data available

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion limits : No data available

9.2. Other information

VOC content : 5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

2-Ethylhexyl Nitrate (27247-96-7)	
LD50 oral rat	> 9640 mg/kg (Rat)
LD50 dermal rabbit	> 4820 mg/kg (Rabbit)
Butyl Glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
1,2,4-Trimethylbenzene (95-63-6)	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
Xylene, Mixture of Isomers (1330-20-7)	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200.000000 mg/kg (Rabbit; Experimental value; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
Vinyl Acetate (108-05-4)	
LD50 oral rat	2900 mg/kg (Rat; Weight of evidence; 3470 mg/kg bodyweight; Rat)
LD50 dermal rabbit	2340 mg/kg (Rabbit; Experimental value; 7440 mg/kg bodyweight; Rabbit)
LC50 inhalation rat (mg/l)	> 11.4 mg/l/4h (Rat; Weight of evidence; 15.81 mg/l/4h; Rat)
LC50 inhalation rat (ppm)	> 3200 ppm/4h (Rat; Weight of evidence; 4490 ppm/4h; Rat)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects. Based on available data, the classification criteria are not met

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Suspected of causing cancer.

Butyl Glycoether (111-76-2)	
IARC group	3
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
IARC group	3
Xylene, Mixture of Isomers (1330-20-7)	
IARC group	3
Ethylbenzene (100-41-4)	
IARC group	2B
Vinyl Acetate (108-05-4)	
IARC group	2B
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause irritation or asthma-like symptoms. May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause slight irritation . May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: May cause slight eye irritation . May cause slight irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

2-Ethylhexyl Nitrate (27247-96-7)	
Threshold limit algae 1	3.22 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Butyl Glycoether (111-76-2)	
LC50 fish 1	1474 ppm (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Static system; Fresh water; Experimental value)
EC50 Daphnia 1	1550 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	911 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Threshold limit algae 2	88 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
1,2,4-Trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	2.356 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)
Ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)
Vinyl Acetate (108-05-4)	
LC50 fish 2	14 - 44 mg/l (LC50; 96 h)

12.2. Persistence and degradability

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.	
Persistence and degradability	Not established.
2-Ethylhexyl Nitrate (27247-96-7)	
Persistence and degradability	Not readily biodegradable in water.
Butyl Glycoether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance
Xylene, Mixture of Isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.
Ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 (20 days)
Vinyl Acetate (108-05-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. Photolysis in the air.
ThOD	1.7 g O ₂ /g substance
12.3. Bioaccumulative potential	
THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.	
Bioaccumulative potential	Not established.
2-Ethylhexyl Nitrate (27247-96-7)	
Log Pow	5.24 (Test data; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
Butyl Glycolether (111-76-2)	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
Log Pow	2.1 - 6
1,2,4-Trimethylbenzene (95-63-6)	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Not established.
Xylene, Mixture of Isomers (1330-20-7)	
BCF fish 2	7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Log Pow	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Vinyl Acetate (108-05-4)	
BCF fish 1	3.16 (BCF)
BCF other aquatic organisms 1	2.09 - 2.34 (BCF)
Log Pow	0.73 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
12.4. Mobility in soil	
2-Ethylhexyl Nitrate (27247-96-7)	
Log Koc	Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC); 3.75; Experimental value
Butyl Glycolether (111-76-2)	
Surface tension	0.065 N/m (20 °C; Calculated value)

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethylbenzene (95-63-6)	
Surface tension	0.029 N/m
Log Koc	log Koc,3.04; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
Xylene, Mixture of Isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
Ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
Vinyl Acetate (108-05-4)	
Surface tension	0.024 N/m (20 °C)
Log Koc	Koc,24.21; QSAR

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1993, Flammable Liquids, n.o.s. (Petroleum Distillates, Diesel Fuel Additive), 3, III, Limited Quantity

ICAO/IATA (air): UN1993, Flammable Liquids, n.o.s. (Petroleum Distillates, Diesel Fuel Additive), 3, III, Limited Quantity

IMO/IMDG (water): UN1993, Flammable Liquids, n.o.s. (Petroleum Distillates, Diesel Fuel Additive), 3, III, Limited Quantity

Special Provisions: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable Liquids, n.o.s. (Petroleum Distillates, Diesel Fuel Additive)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672) T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

SECTION 15: Regulatory information

15.1. US Federal regulations

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
1,2,4-Trimethylbenzene (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Xylene, Mixture of Isomers (1330-20-7)	
SARA Section 311/312 Hazard Classes	Fire hazard
Ethylbenzene (100-41-4)	
Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.	
WHMIS Classification	Class B Division 2 - Flammable Liquid
1,2,4-Trimethylbenzene (95-63-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Ethylbenzene (100-41-4)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Muta.Cat.2; R46

R44

R10

R52/53

Full text of R-phrases: see section 16

15.2.2. National regulations

Ethylbenzene (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

15.3. US State regulations

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

2-Ethylhexyl Nitrate (27247-96-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Butyl Glycolether (111-76-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

1,2,4-Trimethylbenzene (95-63-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene, Mixture of Isomers (1330-20-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Ethylbenzene (100-41-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	
Vinyl Acetate (108-05-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Ethylbenzene (100-41-4)				
State or local regulations				
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)				

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 2 Moderate Hazard

Physical

: 0 Minimal Hazard

Personal Protection

: B

SDS US (GHS HazCom 2012) - TCC

THROTTLE MUSCLE 8 IN 1 DIESEL FUEL SYSTEM CLEANER 16 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.